eneo IAD-5SG1008MUA

SKU: 216472



Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Main Features

- Gigabit PoE Switch, desktop application
- Gigabit Uplink Ports: 1x RJ45, 1x SFP
- 8x 10/100/1000 PoE Ports, IEEE 802.3af/at
- Up to 30W per Port, Total ≤120W
- ESD protection IEC61000-4-2 Standard
- CCTV mode allows transmission up to 250m @ 10Mbps
- Brackets and 150W power-adaptor scope of supply

Specifications

General	
Number of PoE ports	8
Design	Desktop
Dimensions (WxHxD) (extended)	27x200x101,8mm
Weight	500 kg
Type	Layer2 Switch
Mounting type	Desktop
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC
Temperature Range (Operating)	-10°C ~ +45°C
Notes	

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IAD-5SG1008MUA

Remark	CCTV mode: transmission of 10Mbps @ 250m,CCTV mode,PoE Power output: 29.2W @ 1m; 25.8W @ 100m; 24.2W @ 150m; 19.9W @ 250m

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IAD-5SG1008MUA

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-TX, 1x 1000Base-X SFP, 8x 10/100/1000Base-T
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Security	CCTV mode
Internal Switching Capacity (Gbit)	20 Gbps
Internal Switching Capacity (MP per second)	14.9 Mpps
Product labeling:	
Manufacturer order number	216472
Series	eneo Switch

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved