



ISD-55P0010P0A

SKU: 217871



1/1.8" Network Dome, Fixed, Day&Night, 2592x1944, 360°, H.264, 1.05mm, Indoor

Main Features

1/1.8" Sony STARVIS CMOS-Sensor	Compression H.264/MJPEG, Web Casting
1.05mm fixed lens FishEye camera	Cross Web-Browsing
360° Panorama view	D-WDR (Digital Wide Dynamic Range)
Integration in eneo Center Software	Framerate increase on motion detection
True Day&Night	OpenVPN support
Resolution max. 2048x1536@15fps	Compact design for indoor application

Specifications

Dimensions (HxWxD)	63,8x119mm
Series	eneo SN-Series
Camera Type	Fisheye Kamera
Resolution Standard	5 Megapixel
System	True Day&Night
Sensor size	1/1.8"
Imager	CMOS
Video compression	H.264, M-JPEG
Image resolution max.	2592x1944
Image Transmission Rate	15 fps

ISD-55P0010P0A

Continuation of the specifications

Day&Night switch	ICR
Sensitivity	0,3 Lux at F2,8
Low Speed Shutter	no
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Lens Type	fixed focal length
Focal Length	1,05 mm
Digital Zoom	yes
Observe (62 px/m)	14 m
Recognize (125 px/m)	6 m
Identify (250 px/m)	4 m
Detect (25px/m)	36 m
Horizontal Angle of View	360°
Vertical Angle of View	360°
Illumination	no
Housing	Indoor
Color (housing)	white
Housing material	Plastic
Heater	no
Blower	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, Tampering protection
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	5.3W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-10°C ~ +50°C
ONVIF	ONVIF Profile S
Camera type	Dome
Audio	2 Way Audio
Remote configuration	Browser
Weight	270g
Manufacturer order number	217871

ISD-55P0010P0A

Continuation of the specifications

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug

Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update
214441	CUS-SL-GK	Painting basic costs once per RAL color and delivery lot
211124	CUS-SL-P	Extra charge for special paint PTZ dome or panoramic camera in RAL color

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

