eneo ISD-55P0010P0A

SKU: 217871



1/1.8" Network Dome, Fixed, Day&Night, 2592x1944, 360°, H.264, 1.05mm, Indoor

Main Features

1/1.8" Sony STARVIS CMOS-Sensor	Compression H.264/MJPEG, Web Casting
1.05mm fixed lens FishEye camera	Cross Web-Browsing
360° Panorama view	D-WDR (Digital Wide Dynamic Range)
Integration in eneo Center Software	Framerate increase on motion detection
True Day&Night	OpenVPN support
Resolution max. 2048x1536@15fps	Compact design for indoor application

Specifications

General	
Heating	No
Lighting	No
Dimensions (WxHxD) (extended)	63,8x119mm
Weight	0.27 kg
SDK/API	upon request
Text overlay	available
Color (Housing)	white
Housing type	Inside
Housing material	Plastic

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISD-55P0010P0A

Continuation of the specifications

Camera Type	Fisheye Camera
Power consumption	5.3 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S
Power over Ethernet	IEEE 802.3af
Power supply	12VDC, Poe
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	No
Resolution standard	5 MP
Recording sensor	CMOS
Chip size	1/1,8"
Camera shape	Minsters
Day/night mode	Automatic,Day,Night
White balance	Automatic,fluorescent,Outdoor,Manual,Light bulb
Photosensitivity	0,3 Lux bei F2,8
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (63px/m)	14 m
Detect (125px/m)	6 m
Identify (250px/m)	4 m
Perceiving (25px/m)	36 m
Functions	
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card),E-Mail,FTP,Boost,HTTP,TCP,UDP,HTTPS,XML,alarm out
Audio	2 Way Audio
Browser	Edge: MJPEG setup limited, Google Chrome: MJPEG setup limited, Mozilla: MJPEG setup limited, Safari: MJPEG setup limited
Menu languages	Chinese, English, French, German, Japanese, Korean, Russian
Internal memory	microSDHC card, microSDXC card

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISD-55P0010P0A

Continuation of the specifications

Notes	
Remark	To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necessary,we offer a compatibility check
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	Alarm output,Alarm input,Audio input/output,RJ-45,12VDC input (DC plug),connection cable approx.40cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	360°
Vertical angle of view	360°
Focal length	1,05 mm
Lens Type	Prime lens
Zoom Factor (Digital)	0
Video	
Image transfer rate max.	15 fps
Resolution (extended)	2592x1944 (4:3),2048x1536 (4:3),1944x1944,1440x1440,1280x1024 (5:4),1280x960 (4:3),1024x1024,1024x768 (4:3),720x720,704x576 (4:3),640x480 (4:3)
Data stream types	2x H.264,1x MJPEG simultan
Video Compression	H.264, M-JPEG
Product labeling:	
Manufacturer order number	217871
Series	eneo SN-Serie

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISD-55P0010P0A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved