



# eneo ISD-55P0010P0A

SKU: 217871



1/1.8" Network Dome, Fixed, Day&Night, 2592x1944, 360°, H.264, 1.05mm, Indoor

## Main Features

1/1.8" Sony STARVIS CMOS-Sensor

1.05mm fixed lens FishEye camera

360° Panorama view

Integration in eneo Center Software

True Day&Night

Resolution max. 2048x1536@15fps

Compression H.264/MJPEG, Web Casting

Cross Web-Browsing

D-WDR (Digital Wide Dynamic Range)

Framerate increase on motion detection

OpenVPN support

Compact design for indoor application

## Specifications

General	
Heating	No
Lighting	No
Dimensions (WxHxD) (extended)	63,8x119mm
Weight	0.27 kg
SDK	upon request
Text overlay	available
Color (Housing)	white
Housing type	Inside
Housing material	Plastic

# eneo ISD-55P0010P0A

Continuation of the specifications

Camera Type	Fisheye Camera
Power consumption	5.3 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S
Power over Ethernet	IEEE 802.3af
Power supply	12VDC, Poe
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
<b>Camera</b>	
Resolution standard	5 MP
Recording sensor	CMOS
Chip size	1/1,8"
Camera shape	Minsters
Day/night mode	Automatic, Day, Night
White balance	Automatic, fluorescent, Outdoor, Manual, Light bulb
Photosensitivity	0,3 Lux bei F2,8
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	2592x1944
<b>DORI</b>	
Watch (62px/m)	14 m
Detect (125px/m)	6 m
Identify (250px/m)	4 m
Perceiving (25px/m)	36 m
<b>Functions</b>	
Audio support	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card), E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out
Audio	2 Way Audio
Browser	Edge: MJPEG setup limited, Google Chrome: MJPEG setup limited, Mozilla: MJPEG setup limited, Safari: MJPEG setup limited
Menu languages	Chinese, English, French, German, Japanese, Korean, Russian
Internal memory	microSDHC card, microSDXC card
<b>Notes</b>	

## eneo ISD-55P0010P0A

Remark	To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necessary,we offer a compatibility check
--------	---

# eneo ISD-55P0010P0A

Continuation of the specifications

<b>Interfaces / Inputs/ Outputs</b>	
Alarm inputs	1
External connections	Alarm output,Alarm input,Audio input/output,RJ-45,12VDC input (DC plug),connection cable approx.40cm
Control Interfaces	Ethernet
<b>Parts supplied</b>	
Scope of delivery	manual,bag of screws
<b>Lens</b>	
Horizontal angle of view	360°
Vertical angle of view	360°
Focal length	1,05 mm
Lens Type	Prime lens
Zoom Factor (Digital)	0
<b>Video</b>	
Image transfer rate max.	15 fps
Resolution (extended)	2592x1944 (4:3),2048x1536 (4:3),1944x1944,1440x1440,1280x1024 (5:4),1280x960 (4:3),1024x1024,1024x768 (4:3),720x720,704x576 (4:3),640x480 (4:3)
Data stream types	2x H.264,1x MJPEG simultan
Video Compression	H.264, M-JPEG
<b>Product labeling:</b>	
Manufacturer order number	217871
Series	eneo SN-Serie

## Your contact person

VIDEOR E. Hartig GmbH  
 Carl-Zeiss-Straße 8  
 63322 Rödermark  
 Germany

