



# eneo MPP-72A0020MIA

SKU: 219809



1/2,8" HD Analogue Dome, PTZ, Day&Night, 20x, 4,7-94mm, WDR 1920x1080, Infrared, IP66

## Main Features

- 1/2,8" Sony STARVIS CMOS-Sensor
- 20x Auto Focus Zoom, 4.7 ~ 94mm / 16x Digital
- Resolution max. 1920x1080 (Full HD)
- Separate outputs for HD signals and composite
- Signal formats: HD-TVI, AHD selectable, composite

- Real time WDR (Wide Dynamic Range) 25 / 30fps
- Integrated infrared lighting (up to 60m)
- 3D DNR noise reduction, auto-calibration
- Protected areas, Defog function
- Alarm inputs and outputs, 12VDC, IP66

## Specifications

General	
Heating	No
Lighting	Infrared
Dimensions (WxHxD) (extended)	208,3x182,4mm
Illumination range	ca. 60m
Weight	2.8 kg
Text overlay	available
Color (Housing)	white,black
Housing type	Outside
Housing material	Aluminium
Power consumption	18 W
Mounting type	Ceiling, Wall

# eneo MPP-72A0020MIA

Continuation of the specifications

Protection	IP66
Power supply	12VDC
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	WDR 120dB
<b>Camera</b>	
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	PTZ
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night
White balance	Automatic,Manual,Light bulb,Fluorescent light,Outdoor
Photosensitivity	0,35 Lux bei F1,6,50 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	1280x720,720x576,1920x1080
<b>DORI</b>	
Watch (62px/m)	28 - 550 m
Detect (125px/m)	13 - 270 m
Identify (250px/m)	7 - 130 m
Perceiving (25px/m)	70 - 1370 m
<b>Functions</b>	
Digital Noise Reduction (DNR)	Yes
Turning range	360 °
Home Position	Multiple actions adjustable
Menu languages	English, French, German, Italian, Polish, Portuguese, Spanish
Tours	8 selectable tours
Speed (manual control)	380 °/sec
Speed (Target Approach)	380 °
<b>Interfaces / Inputs/ Outputs</b>	
Alarm inputs	4
Number of alarm outputs	2
External connections	Alarm in/output,voltage input,RS-485,Composite (FBAS),HD-TVI / AHD BNC,connection cable approx.25cm
Interface Protocols	Fastrax IIIIE, Pelco D, UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol), RS-485
<b>Parts supplied</b>	
Scope of delivery	manual,plug set,bag of screws

# eneo MPP-72A0020MIA

Continuation of the specifications

<b>Lens</b>	
Horizontal angle of view	55,5 - 3°
Vertical angle of view	32,4 - 1,7°
Focal length	4,7 - 94 mm
Aperture Range (F)	F1.6~F3.0
Lens Type	Auto Focus Zoom
Zoom Factor (Digital)	16
Zoomfactor (optical)	20
<b>Video</b>	
Signal Format	AHD @ 2MP, Composite (FBAS), HD-TVI @ 2MP
<b>Product labeling:</b>	
Manufacturer order number	219809
Series	eneo COAXIZE

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

