

eneo ISD-59P0010P0A

SKU: 220196



1/1,7" Network Dome, fixed, Day/Night, 4000x3000, H.265, 1,29mm, 360°, infrared, IP66

Main Features

1/1.7" Sony STARVIS CMOS-Sensor	Quad Stream (H.264/H.265x3, MJPEGx1)
1.29mm fixed lens FishEye camera	Cross Web-Browsing
360° Panorama-, Corridor-, Quad-, Panomorph-View, ceiling TrueWDR (Digital Wide Dynamic Range)	
Integration in eneo Center Software	Framerate increase on motion detection (Smart Codec)
True Day & Night	IR-LED Illumination integrated
Resolution max. 4000x3000@20fps	Compact design for indoor application

Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	58,7x151,4mm
Weight	0.75 kg
Text overlay	available
Color (Housing)	white
Housing material	Metal
Camera Type	Fisheye Camera

eneo ISD-59P0010P0A

Continuation of the specifications

Power consumption	15 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP66
Power supply	12VDC, Poe
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	WDR 120dB
Certifications	IK10
Camera	
Resolution standard	8 MP
Recording sensor	CMOS
Chip size	1/1,7"
Camera shape	Minsters
Day/night mode	Automatic,Day,Night
White balance	Automatic,fluorescent,Manual,Outdoor,incandescent
Photosensitivity	0,3 Lux bei F2,8
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	4000x3000
DORI	
Watch (62px/m)	25 m
Detect (125px/m)	11 m
Identify (250px/m)	5 m
Perceiving (25px/m)	60 m
Functions	
Audio support	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card),E-Mail,FTP,Boost,HTTP,TCP,UDP,HTTPS,XML,alarm out
Audio	2 Way Audio
Browser	Edge: MJPEG setup limited, Google Chrome: MJPEG setup limited, Mozilla: MJPEG setup limited, Safari: MJPEG setup limited
Menu languages	Chinese, English, French, German, Japanese, Korean, Russian
Internal memory	microSD card, microSDXC card
Notes	

eneo ISD-59P0010P0A

Remark	To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necessary,we offer a compatibility check
--------	---

eneo ISD-59P0010P0A

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	Alarm output,Alarm input,Audio input/output,RJ-45,12VDC input (DC plug),connection cable approx.40cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	360°
Focal length	1,29 mm
MOD (Minimum Object Distance)	0.1 m
Lens Type	Prime lens
Zoom Factor (Digital)	0
Video	
Image transfer rate max.	30 fps
Resolution (extended)	4000x3000 (4:3),3000x3000,2560x2560,2160x2160,2048x2048,1280x1280,640x640,480x480
Data stream types	Quad Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	220196
Series	eneo SN-Serie

Your contact person

VIDEOR E. Hartig GmbH
 Carl-Zeiss-Straße 8
 63322 Rödermark
 Germany

