


eneo IPP-88A0030MIA

SKU: 220203



1/1,7" Network Dome, PTZ, Day&Night, 30x, H.265, WDR, 3840x2160, Infrared, IP66

Main Features

1/1,7" Sony STARVIS CMOS-Sensor

8.0MP 3840x2160 Pixel, 25/30fps

30x AF Zoom, 6~180mm

Quad Stream H.265, H.264, MJPEG (Smart Codec)

Real time WDR (Wide Dynamic Range) 25/30fps

Intelligent self learning video analysis

Digital Noise Reduction (2DNR/3DNR)

Audio support including audio alarm

Infrared illumination up to 200m

Alarm in- and outputs, micro SD-card

Power supply 12VDC or UPoE (High-PoE Midspan included)

Support ONVIF Profile S und Profile T

Specifications

General	
Heating	No
Lighting	Infrared
Dimensions (WxHxD) (extended)	317,8x201.8mm
Weight	5.1 kg
SDK	upon request
Text overlay	available
Color (Housing)	white,black
Housing type	Outside
Housing material	Aluminium

eneo IPP-88A0030MIA

Continuation of the specifications

Power consumption	28 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	HiPoE+
Protection	IP66
Power supply	12VDC, Poe
Temperature Range (Operating)	-30°C ~ +55°C
Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	8 MP
Recording sensor	CMOS
Chip size	1/1,7"
Flickerless function	Yes
Camera shape	PTZ
Signal-to-noise ratio	52 dB
Day/night mode	Day,Night,Automatic
White balance	Automatic,Manual
Photosensitivity	0,75 Lux bei F1,6,50 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	3840x2160
DORI	
Watch (62px/m)	61 - 1310 m
Detect (125px/m)	29,6 - 645 m
Identify (250px/m)	14,4 - 327,1 m
Perceiving (25px/m)	153 - 3210 m
Functions	
Analysis	Loitering Detection, Manipulation (TD), Motion Detection
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Turning range	360 °
Alarm processing	recording internal storage (SD card),E-Mail,FTP,Boost,HTTP,TCP,UDP,HTTPS,XML,alarm out
Audio	2 Way Audio
Browser	Edge: MJPEG setup limited, Google Chrome: MJPEG setup limited, Mozilla: MJPEG setup limited, Safari: MJPEG setup limited

eneo IPP-88A0030MIA

Continuation of the specifications

Home Position	Selectable, Tour, Preset, Pattern
Menu languages	Chinese, English, French, German, Japanese, Korean, Russian
Password	Administrator and User
Tours	8 selectable tours
Vertical tilt range	-10° ~ +90°
Speed (manual control)	380 °/sec
Speed (Target Approach)	380 °/sec
Internal memory	microSDHC card, microSDXC card
Notes	
Remark	To ensure a faultless PoE operation, please use only the supplied HiPoE+ Midspan of accessories pack., To guarantee you an optimum user experience, we recommend that you only use components of the same brand in a system. If several brands are used in combin
Interfaces / Inputs/ Outputs	
Alarm inputs	4
External connections	Alarm output, Alarm input, Audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx. 40cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual, HiPoE+ Midspan (Power 100-240VAC, Operation Temperature 0°~40°), plug set
Lens	
Horizontal angle of view	55,4 - 2,7°
Vertical angle of view	31,1 - 1,5°
Focal length	6 - 180 mm
MOD (Minimum Object Distance)	1 m
Lens Type	Auto Focus Zoom
Zoom Factor (Digital)	0
Zoomfactor (optical)	30
Video	
Image transfer rate max.	30 fps
Resolution (extended)	3840x2160 (16:9), 3072x2048 (4:3), 2592x1944 (4:3), 2592x1520 (16:9), 2560x1440 (16:9), 1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 80
Data stream types	Quad Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	220203

eneo IPP-88A0030MIA

Continuation of the specifications

Series	eneo SN-Serie
--------	---------------

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

