



# eneo IAM-5SE1004MUC

SKU: 220212



Gigabit Switch, Unmanaged, 4x PoE, 2x RJ45 and 2x SFP, 1000Mbps, Industrial Design

## Main Features

Gigabit PoE switch, DIN Rail

Gigabit Uplink ports 2xRJ45, 2xSFP

4x 10/100/1000 PoE Ports, IEEE 802.3af/at

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

Temperature range -40° C ~ +75° C

## Specifications

General	
Number of PoE ports	4
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	46x110x163mm
Application environment	inside
Weight	530 kg
Type	Unmanaged
Mounting type	DIN Rail, Wall
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC
Temperature Range (Operating)	-40°C ~ +75°C
Notes	
Remark	External power supply specification: 100~240VAC, 150W, 30x70x150mm, -30°~+70°

# eneo IAM-5SE1004MUC

Continuation of the specifications

<b>Interfaces / Inputs/ Outputs</b>	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	2x 10/100/1000Base-TX, 2x 10/100/1000T SFP, 4x 10/100/1000Base-T
<b>Parts supplied</b>	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
<b>Network</b>	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX
Internal Switching Capacity (Gbit)	14 Gbps
Internal Switching Capacity (MP per second)	10.4 Mpps
<b>Product labeling:</b>	
Manufacturer order number	220212
Series	eneo Switch

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

