

# eneo IAD-5SE1008MUA

SKU: 220593



Switch, Unmanaged, 120W 8x PoE, 2 x RJ45 Uplink  
10/100/1000 Mbps, Desktop

## Main Features

Ethernet PoE Switch, desktop application

Gigabit Uplink Ports: 2 x RJ45

8 x 10/100 PoE Ports IEEE 802.3af/at

Up to 30W per Port, Total  $\leq 120W$

Surge protection IEC61000-4-5 (6KV)

CCTV mode allows transmission up to 250m @ 10Mbps

Plug and Play no further settings necessary

## Specifications

| General                       |                            |
|-------------------------------|----------------------------|
| Number of PoE ports           | 8                          |
| Design                        | Desktop                    |
| Dimensions (WxHxD) (extended) | 27x200x101,8mm             |
| Weight                        | 500 kg                     |
| Type                          | Unmanaged                  |
| Mounting type                 | Desktop                    |
| PoE Budget (Total)            | 120 W                      |
| Power over Ethernet           | IEEE 802.3af, IEEE 802.3at |
| Power supply                  | 48-57 VDC                  |
| Temperature Range (Operating) | -10°C ~ +55°C              |
| <b>Notes</b>                  |                            |

## eneo IAD-5SE1008MUA

|        |   |
|--------|---|
| Remark | CCTV mode: transmission of 10Mbps @ 250m, CCTV mode, PoE Power output: 29.2W @ 1m; 25.8W @ 100m; 24.2W @ 150m; 19.9W @ 250m |
|--------|---|

# eneo IAD-5SE1008MUA

Continuation of the specifications

|   |   |
|---|---|
| <b>Interfaces / Inputs/ Outputs</b>         |   |
| Ethernet interface                          | 1000Base-T, 100Base-TX, 10Base-T          |
| Ports                                       | 2x 10/100/1000Base-T, 8x 10/100Base-TX    |
| <b>Parts supplied</b>                       |   |
| Scope of delivery                           | manual,PSU                                |
| <b>Network</b>                              |   |
| Eneo _netzwerkstandards                     | IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX |
| Security                                    | CCTV mode                                 |
| Internal Switching Capacity (Gbit)          | 5.6 Gbps                                  |
| Internal Switching Capacity (MP per second) | 4.2 Mpps                                  |
| <b>Product labeling:</b>                    |   |
| Manufacturer order number                   | 220593                                    |
| Series                                      | eneo Switch                               |

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

