



eneo IPD-78M3611M0A

SKU: 220930



1/2,5" Network Dome, Fix, 3840x2160, Day&Night, DOL-WDR 3,6-11mm, Infrared, IP67

Main Features

- 1/2.5" Sony STARVIS CMOS sensor
- Resolution max. 3840x2160, 8 Megapixel
- Motorised varifocal lens 3,6~11mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- VCA video analysis, ONVIF event mapping
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Smart Codec H.265 ROI (Region of interest)
- Quad Smart Streaming: H.265(+), H.264(+), MJPEG
- Slot for Micro SD Card, HTML5 replay, Audio, Alarm
- Power supply PoE, 12VDC or 24VAC
- For outdoor use IP66, vandal proofed IK10
- Supports ONVIF Profile S and Profile T

Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	119x140mm
Weight	1 kg
SDK	upon request
Text overlay	available
Color (Housing)	Pantone Cool Gray 1C
Color (dome)	clear

eneo IPD-78M3611M0A

Continuation of the specifications

Housing type	Inside, Outside
Housing material	Aluminium
Power consumption	10.8 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67
Power supply	12VDC, 24VAC, PoE
Temperature Range (Operating)	-50°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Certifications	IK10
Camera	
Resolution standard	8 MP
Recording sensor	CMOS
Chip size	1/2,5"
Flickerless function	Yes
Camera shape	Minsters
Signal-to-noise ratio	50 dB
Day/night mode	Automatic, Day, Night, night-color mode, extern (Sensor)
White balance	ATW-Indoor, ATW-Outdoor, Manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes
Photosensitivity	0,2 Lux bei F1,5,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	3840x2160
DORI	
Watch (62px/m)	36,6 - 86,5 m
Detect (125px/m)	17,7 - 42,6 m
Identify (250px/m)	8,6 - 21,2 m
Perceiving (25px/m)	91,7 - 214 m
Functions	
Audio support	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Turning range	173 °
Alarm processing	recording internal storage (SD card), E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out
Audio	2 Way Audio
Browser	Edge: MJPEG, Mozilla: MJPEG, Safari: MJPEG

eneo IPD-78M3611M0A

Continuation of the specifications

Menu languages	English, French, German, Korean
Password	Administrator and User
Vertical tilt range	65 °(25 ~ 90°)
Internal memory	microSDHC card, microSDXC card
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	micro SD card slot,Alarm in/output,RJ-45,Combi connector,connection cable approx.15cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	84 - 40°
Vertical angle of view	46 - 21°
Focal length	3,6 - 11 mm
MOD (Minimum Object Distance)	0.5 m
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	3
Video	
Image transfer rate max.	30 fps
Resolution (extended)	3840x2160 (16:9),2592x1520 (16:9),1920x1080 (16:9),1600x900 (16:9),1280x720 (16:9),960x540 (16:9),640x360 (16:9),320x180 (16:9)
Data stream types	Multi-Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	220930
Series	eneo LN-Serie

Optional Accessory

SKU	Name	Description
209832	eneo AK-5	Camera Junction Box, for Callisto Dome series, IP66
216923	eneo DOME-S1	Sun Shield for eneo Callisto Dome Series
215644	eneo DOME-WB3	Wall bracket for eneo Dome Cameras MED-62xxxxxM0A and IED-62xxxxxM0A
209831	eneo DOME/BASIS1	Surface mount base , Callisto Dome line
207192	eneo DOME/WEDGE2	Wedge Adapter, Callisto Dome Line
221334	eneo IAM-4MU1001M0A	EPOC Signal Converter, BNC to 2-wire cable transmission for EPOC Cameras, Transceiver
218218	eneo Site Manager	Management Software for eneo IP products

eneo IPD-78M3611M0A

Continuation of accessory

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

