



# eneo AES-5SF0036M0A

SKU: 221517



1/3" Mini Dome, Fix, clear 3,6mm, 960TVL, 12VDC, vandalism protect, flush mount

## Main Features

1/3" Fix dome camera with Sony CCD

Integrated lens F2.0/3.6mm

Resolution of 960 horizontal lines

Automatic shutter control

Digital signal processing (DSP)

Automatic white balance (ATW)

White-coloured aluminium die-cast casing

Clear Lexan bubble, 57mm

Easy indoor installation

For in-ceiling flush mounting

Vandal resistant

## Specifications

| General                       |           |
|-------------------------------|-----------|
| Heating                       | No        |
| Vandalism-resistant           | Yes       |
| Lighting                      | No        |
| Dimensions (WxHxD) (extended) | 58,5x88   |
| Weight                        | 0.2 kg    |
| Color (Housing)               | white     |
| Color (dome)                  | clear     |
| Housing type                  | Outside   |
| Housing material              | Aluminium |

## eneo AES-5SF0036M0A

Continuation of the specifications

|                                     |   |
|-------------------------------------|---|
| Camera Type                         | Domecamera  |
| Power consumption                   | 1.2 W   |
| Mounting type                       | Ceiling installation  |
| Protection                          | IP66  |
| Power supply                        | 12VDC   |
| Temperature Range (Operating)       | -10°C ~ +50°C   |
| <b>Camera</b>                       |   |
| Backlight compensation              | Yes   |
| Low Speed Shutter                   | No  |
| Recording sensor                    | CCD   |
| Chip size                           | 1/3"  |
| Camera shape                        | Minsters  |
| Signal-to-noise ratio               | 50 dB   |
| Day/night mode                      | Automatic   |
| White balance                       | ATW   |
| Photosensitivity                    | 0,1 Lux bei F1,2,50 IRE   |
| System                              | Electronic Day&Night  |
| Day/night switching                 | Electronic  |
| <b>DORI</b>                         |   |
| Watch (62px/m)                      | 12,6 m  |
| Detect (125px/m)                    | 5,9 m   |
| Identify (250px/m)                  | 2,8 m   |
| Perceiving (25px/m)                 | 32,2 m  |
| <b>Functions</b>                    |   |
| Motion detector                     | No  |
| Digital Noise Reduction (DNR)       | Yes   |
| <b>Interfaces / Inputs/ Outputs</b> |   |
| Alarm inputs                        | 0   |
| Number of alarm outputs             | 0   |
| External connections                | 12VDC input (DC plug),Composite (FBAS),connection cable approx.25cm |
| Control Interfaces                  | no  |
| Video Outputs                       | Composite (FBAS)  |
| <b>Parts supplied</b>               |   |
| Scope of delivery                   | manual,screw set,bag of screws                                      |
| <b>Lens</b>                         |   |
| Horizontal angle of view            | 68°   |
| Focal length                        | 3,6 mm  |
| Lens Type                           | Prime lens  |
| Zoom Factor (Digital)               | 0   |
| <b>Video</b>                        |   |
| Horizontal resolution               | 960 TVL   |

## eneo AES-5SF0036M0A

Continuation of the specifications

|                           |              |
|---------------------------|--------------|
| <b>Product labeling:</b>  |              |
| Manufacturer order number | 221517       |
| Series                    | eneo COAXIZE |

### Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

