

# eneo IAM-5SE1004MUP

SKU: 221889



Gigabit Switch, Unmanaged 60W, 4x PoE, Industrial Design -40°C~+75°C, PD port

## Main Features

- Gigabit PoE Switch, DIN Rail
- 4x 10/100/1000 PoE Ports, IEEE 802.3ab/af/at/u
- 1 x SFP Gigabit uplink port
- 1 x RJ45 Gigabit uplink port, PD-capable (60W PoE input)

- PoE watchdog (reboot automatically)
- Surge protection IEC61000-4-5 (6KV)
- Temperature range -40° C ~ +75° C

## Specifications

General	
Number of PoE ports	4
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	46x110x163mm
Application environment	inside
ESD protection	IEC61000-4-2
Weight	540 kg
Type	Unmanaged
Power consumption	60 W
Mounting type	DIN Rail
PoE Budget (Total)	60 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-56VDC, Poe

# eneo IAM-5SE1004MUP

Continuation of the specifications

Temperature Range (Operating)	-40°C ~ +75°C
<b>Notes</b>	
Remark	We recommend the use edp. number: 216568 PoE Injector NE-60PoE to ensure an interference-free function with power supply via PD port
<b>Interfaces / Inputs/ Outputs</b>	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-T (PoE-PD), 1x 1000Base-X SFP, 4x 10/100/1000Base-T
<b>Parts supplied</b>	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
<b>Network</b>	
VLAN	Yes
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Internal Switching Capacity (Gbit)	12 Gbps
Internal Switching Capacity (MP per second)	8.9 Mpps
<b>Product labeling:</b>	
Manufacturer order number	221889
Series	eneo Switch

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

