

eneo IAM-5SE1004MUP

SKU: 221889



Gigabit Switch, Unmanaged 60W, 4x PoE, Industrial Design -40°C~+75°C, PD port

Main Features

- Gigabit PoE Switch, DIN Rail
- 4x 10/100/1000 PoE Ports, IEEE 802.3ab/af/at/u
- 1 x SFP Gigabit uplink port
- 1 x RJ45 Gigabit uplink port, PD-capable (60W PoE input)

- PoE watchdog (reboot automatically)
- Surge protection IEC61000-4-5 (6KV)
- Temperature range -40° C ~ +75° C

Specifications

General	
Number of PoE ports	4
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	46x110x163mm
Application environment	inside
ESD protection	IEC61000-4-2
Weight	540 kg
Type	Unmanaged
Power consumption	60 W
Mounting type	DIN Rail
PoE Budget (Total)	60 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-56VDC, Poe

eneo IAM-5SE1004MUP

Continuation of the specifications

Temperature Range (Operating)	-40°C ~ +75°C
Notes	
Remark	We recommend the use edp. number: 216568 PoE Injector NE-60PoE to ensure an interference-free function with power supply via PD port
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-T (PoE-PD), 1x 1000Base-X SFP, 4x 10/100/1000Base-T
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
VLAN	Yes
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Internal Switching Capacity (Gbit)	12 Gbps
Internal Switching Capacity (MP per second)	8.9 Mpps
Product labeling:	
Manufacturer order number	221889
Series	eneo Switch

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

