



eneo IPP-62A0020M0B

SKU: 222184



1/2,8" Network Dome, PTZ, Day&Night, 20x, H.265, WDR, 1920x1080, PoE, IP66

Main Features

1/2.8" Sony STARVIS CMOS-Sensor

Full HD 1920x1080 Pixel, 25/30fps

23x AF Zoom, 4.7~94mm

Quad Stream H.265, H.264, MJPEG (Smart Codec)

Real time WDR (Wide Dynamic Range) 25/30fps

Intelligent motion detector

Digital Noise Reduction (2DNR/3DNR)

Audio support including audio alarm

Alarm in- and outputs, micro SD-card slot

Power supply 12VDC, 24VAC or PoE

IK10 IK shock resistance degree

Support ONVIF Profile S und Profile T

Specifications

| General | |
|-------------------------------|--------------|
| Heating | No |
| Vandalism-resistant | Yes |
| Lighting | No |
| Dimensions (WxHxD) (extended) | 150x154mm |
| Weight | 1.6 kg |
| SDK | upon request |
| Text overlay | available |
| Color (Housing) | white |
| Color (dome) | clear |

eneo IPP-62A0020M0B

Continuation of the specifications

| | |
|-------------------------------|--|
| Housing type | Inside, Outside |
| Housing material | Aluminium |
| Power consumption | 12 W |
| Mounting type | Ceiling, Wall |
| ONVIF | ONVIF Profile S, ONVIF Profile T |
| Power over Ethernet | IEEE 802.3af |
| Protection | IP66 |
| Power supply | 12VDC, 24VAC, Poe |
| Temperature Range (Operating) | -20°C ~ +50°C |
| Wide Dynamic Range (WDR) | WDR 120dB |
| Certifications | IK10 |
| Camera | |
| Backlight compensation | Yes |
| Low Speed Shutter | Yes |
| Resolution standard | 2 MP |
| Recording sensor | CMOS |
| Chip size | 1/2,8" |
| Flickerless function | Yes |
| Camera shape | PTZ |
| Signal-to-noise ratio | 50 dB |
| Day/night mode | Day,Night,Automatic |
| White balance | Automatic,Manual |
| Photosensitivity | 0,2 Lux bei F1,6,50 IRE |
| System | True Day&Night |
| Day/night switching | Switchable IR Filter (ICR) |
| Display | |
| Image resolution max. | 1920x1080 |
| DORI | |
| Watch (62px/m) | 30,2 - 591,6 m |
| Detect (125px/m) | 14,7 - 292,6 m |
| Identify (250px/m) | 7 - 146 m |
| Perceiving (25px/m) | 75,7 - 1446,5 m |
| Functions | |
| Audio support | Yes |
| Motion detector | Yes |
| Digital Noise Reduction (DNR) | Yes |
| Multicast | Yes |
| Analysis | Manipulation (TD), Motion Detection |
| Turning range | 360 ° |
| Alarm processing | recording internal storage (SD card),E-Mail,FTP,Boost,HTTP,TCP,UDP,HTTPS,XML,alarm out |

eneo IPP-62A0020M0B

Continuation of the specifications

| | |
|-------------------------------------|---|
| Audio | 2 Way Audio |
| Browser | Edge: MJPEG setup limited, Google Chrome: MJPEG setup limited, Mozilla: MJPEG setup limited, Safari: MJPEG setup limited |
| Home Position | Selectable, Tour, Preset, Pattern |
| Menu languages | Chinese, English, French, German, Japanese, Korean, Russian |
| Password | Administrator and User |
| Tours | 8 selectable tours |
| Vertical tilt range | -10° ~ 190° |
| Speed (manual control) | 380 °/sec |
| Speed (Target Approach) | 380 °/sec |
| Internal memory | microSDHC card, microSDXC card |
| Notes | |
| Remark | To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necessary,we offer a compatibility check |
| Interfaces / Inputs/ Outputs | |
| Alarm inputs | 4 |
| External connections | Alarm output,Alarm input,Audio in/output,RJ-45,voltage input,connection cable approx.25cm |
| Control Interfaces | Ethernet |
| Parts supplied | |
| Scope of delivery | manual,plug set,bag of screws |
| Lens | |
| Horizontal angle of view | 55,5 - 3° |
| Vertical angle of view | 32,4 - 1,7° |
| Focal length | 4,7 - 94 mm |
| MOD (Minimum Object Distance) | 1 m |
| Lens Type | Auto Focus Zoom |
| Zoom Factor (Digital) | 16 |
| Zoomfactor (optical) | 20 |
| Video | |
| Image transfer rate max. | 30 fps |
| Resolution (extended) | 1920x1080 (16:9),1440x1080 (4:3),1280x1024 (5:4),1024x768 (4:3),1280x720 (16:9),800x600 (4:3),800x480 (16:9),704x576 (4:3),704x480 (4:3),640x480 (4:3),400x240 (4:3),352x288 (4:3), |
| Data stream types | Quad Streaming |
| Video Compression | H.264, H.264+, H.265, H.265+, M-JPEG |

eneo IPP-62A0020M0B

Continuation of the specifications

| | |
|---------------------------|---------------|
| Product labeling: | |
| Manufacturer order number | 222184 |
| Series | eneo SN-Serie |

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

