



eneo AES-5SF0036M1A

SKU: 223916



1/3" Mini Dome, Fix, clear, 3,6mm, 960TVL, 12VDC, vandalism protect

Main Features

1/3" Fix dome camera with Sony CCD

Integrated lens F2.0/3.6mm

Resolution of 960 horizontal lines

Automatic shutter control

Digital signal processing (DSP)

Automatic white balance (ATW)

White-coloured aluminium die-cast casing

Clear Lexan bubble, 57mm

Easy indoor installation

For wall or ceiling mounting

Vandal resistant

Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	No
Dimensions (WxHxD) (extended)	60,5x80
Weight	0.26 kg
Color (Housing)	white
Color (dome)	clear
Housing type	Outside
Housing material	Aluminium

eneo AES-5SF0036M1A

Continuation of the specifications

Power consumption	1.2 W
Mounting type	Ceiling
Protection	IP66
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	no
Certifications	IK10
Camera	
Recording sensor	CCD
Chip size	1/3"
Camera shape	Minsters
Signal-to-noise ratio	-50 dB
Day/night mode	Automatic
White balance	ATW
Photosensitivity	0,1 Lux bei F1,2,50 IRE
System	Electronic Day&Night
Day/night switching	Electronic
DORI	
Watch (62px/m)	12,6 m
Detect (125px/m)	5,9 m
Identify (250px/m)	2,8 m
Perceiving (25px/m)	32,2 m
Functions	
Digital Noise Reduction (DNR)	Yes
Interfaces / Inputs/ Outputs	
Alarm inputs	0
Number of alarm outputs	0
External connections	12VDC input (DC plug),Composite (FBAS),connection cable approx.25cm
Control Interfaces	no
Parts supplied	
Scope of delivery	manual,screw set,bag of screws
Lens	
Horizontal angle of view	68°
Focal length	3,6 mm
Lens Type	Prime lens
Zoom Factor (Digital)	0
Video	
Horizontal resolution	960 TVL
Product labeling:	
Manufacturer order number	223916
Series	eneo COAXIZE

eneo AES-5SF0036M1A

Continuation of the specifications

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

