



eneo MPP-62A0020M0B

SKU: 226625

EAN: 4260229840351



1/2,8" HD Analogue Dome, PTZ, Day&Night, 20x, 4,7-94mm, 1920x1080, WDR, IP66

Camera not included

Main Features

Attention successor article no. 243176

1/2,8" Sony STARVIS CMOS-Sensor

20x Auto Focus Zoom, 4.7 ~ 94mm / 16x Digital

Resolution max. 1920x1080 (Full HD)

Separate outputs for HD signals and composite

Signal formats: HD-TVI, AHD selectable, composite

Real time WDR (Wide Dynamic Range) 25 / 30fps

Compact design for in- and outdoor applications

3D DNR noise reduction, auto-calibration

Protected areas, Defog function

Alarm inputs and outputs, 12VDC/24VAC, IK10, IP66

Specifications

General	
Fan	Yes
Vandalism-resistant	Yes
Lighting	No
Dimensions (WxHxD) (extended)	150x154mm
Weight	1.6 kg
Text overlay	available
Color (Housing)	white
Color (dome)	clear
Housing type	Inside, Outside

eneo MPP-62A0020M0B

Continuation of the specifications

Housing material	Aluminium
Power consumption	12 W
Mounting type	Ceiling, Wall
Protection	IP66
Power supply	12VDC, 24VAC
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	WDR 120dB
Certifications	IK10
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	PTZ
Signal-to-noise ratio	50 dB
Day/night mode	Automatic, Day, Night
White balance	Automatic, Manual, Light bulb, Fluorescent light, Outdoor
Photosensitivity	0,35 Lux bei F1,6,50 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1280x720, 720x576, 1920x1080
DORI	
Watch (62px/m)	28 - 550 m
Detect (125px/m)	13 - 270 m
Identify (250px/m)	7 - 130 m
Perceiving (25px/m)	70 - 1370 m
Functions	
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Turning range	360 °
Home Position	Selectable, Tour, Preset, Pattern
Menu languages	English, French, German, Italian, Polish, Portuguese, Spanish
Tours	8 selectable tours
Speed (manual control)	380 °/sec
Speed (Target Approach)	380 °
Interfaces / Inputs/ Outputs	
Alarm inputs	4
Number of alarm outputs	2

eneo MPP-62A0020M0B

Continuation of the specifications

External connections	Alarm in/output,voltage input,RS-485,Composite (FBAS),HD-TVI / AHD BNC,connection cable approx.25cm
Interface Protocols	Fastrax, Pelco D, Pelco P, UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol), RS-485
Video Outputs	AHD, Composite (FBAS)
Parts supplied	
Scope of delivery	manual,plug set,bag of screws
Lens	
Horizontal angle of view	55,5 - 3°
Vertical angle of view	32,4 - 1,7°
Focal length	4,7 - 94 mm
Aperture Range (F)	F1.6~F3.0
Lens Type	Auto Focus Zoom
Zoom Factor (Digital)	16
Zoomfactor (optical)	20
Video	
Signal Format	AHD @ 2MP, Composite (FBAS), HD-TVI @ 2MP
Product labeling:	
EAN/GTIN	4260229840351
Manufacturer order number	226625
Series	eneo COAXIZE

Your contact person

VIDEOR E. Hartig GmbH
 Carl-Zeiss-Straße 8
 63322 Rödermark
 Germany

