Solvido SOL-IQbox-maxis-B

SKU: 226950

camera connection box for video security with power plug FI/LS, 500x400x210mm

Main Features

Optimised for outdoor use	Wall or pole mounting
Electrically pre-wired for flexible, modular installation	Quick and easy installation
UV stabilised polycarbonate, corrosion resistant	Simple mechanical processing
Protection class IP 66	Contemporary design
Impact resistance IK 10 vandalism-proof	Service socket, RCD circuit breaker included
Door can be swivelled (with door contact switch)	

Specifications

General	
Power supply	230VAC
Temperature Range (Operating)	-25°C ~ +65°C
Certifications	IK10
Product labeling:	
Manufacturer order number	226950
Series	Solvido IQbox

Optional Accessory

SKU	Name	Description

© Copyright VIDEOR E. Hartig GmbH - September 5, 2026 - technical changes reserved

Solvido SOL-IQbox-maxis-B

Continuation of accessory

211278	jetrics fiber SBT12 Spleißbox	Spleissbox mit Telekom Spleisskassette für 12 Spleisse
210300	jetrics MDR-100-12	Power Supply 12V / 7,5A for DIN rail mounting TS-35
209004	jetrics MDR-100-48	Power Supply 48V / 2A
211604	jetrics MDR-20-12	Power Supply 12VDC / 1,67A for DIN rail mounting TS-35
211055	jetrics MDR-60-12	Power Supply 12VDC / 5A for DIN rail mounting TS-35
211056	jetrics MDR-60-48	Power Supply 48VDC / 1,25A for DIN rail mounting TS-35
236262	Solvido 50W Semiconductor power supply	with thermostat, for DIN rail mounting
211498	Solvido SOL-WST-MB-40	Pole Mount 40cm, set (2pcs) for SOL-IQbox-maxi
220468	Solvido SOL-WST-SH/1	Swivelling lever for profile half-cylinder (1pc.) delivery without lock cylinder
219464	Solvido SOL-WST-SSK-ES-40	
220068	Solvido SOL-WST-SSK/1	Lock with toggle lock (1 piece) with key, for CUS-WST and SOL-IQbox series
209743	Solvido SOL-WST-WB	Wall mounting for CUS-WST and SOL-IQbox series set (4pcs) wall clearance 10mm

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

VIDEOR

© Copyright VIDEOR E. Hartig GmbH - September 5, 2026 - technical changes reserved