# eneo ISD-52F0023WSA

SKU: 227007

Camera not included

1/2,8" Netzwork Dome, WDR, 1920x1080, Day&Night, 2,3mm H.265, PoE, 12VDC, Surface, IK10

## Main Features

| | |
|---|---|
| 1 / 2.8 "2.0 MP Sony STARVIS CMOS sensor | Slot for micro SD memory card |
| Resolution max. 1920x1080 (Full HD) | ONVIF compliance, PoE IEEE802.af, 12VDC |
| Fixed focal length 2.3mm, day / night lens (HFoV 135 °!) | Audio, alarm inputs and outputs |
| Quad Streaming (H.265, H.264, MJPEG) | Privacy zones, password protection, browser-independent |
| Intelligent self-learning video analysis (IntelliVision inside) | Increasing the refresh rate when moving |
| WDR 120dB, Smart BLC | Suitable for indoor and outdoor use IP66 |

## Specifications

| **General** | |
|---|---|
| Heating | No |
| Vandalism-resistant | Yes |
| Lighting | No |
| Dimensions (WxHxD) (extended) | 91,5x120mm |
| Weight | 0.88 kg |
| SDK | upon request |
| Text overlay | available |
| Color (Housing) | white |
| Color (dome) | clear |

© Copyright VIDEOR E. Hartig GmbH - September 16, 2026 - technical changes reserved

# eneo ISD-52F0023WSA

Continuation of the specifications

| | |
|---|---|
| Housing type | Outside |
| Housing material | Aluminium |
| Power consumption | 4.8 W |
| Mounting type | Ceiling, Wall |
| ONVIF | ONVIF Profile S, ONVIF Profile T |
| Power over Ethernet | IEEE 802.3af |
| Protection | IP66 |
| Power supply | 12VDC, Poe |
| Temperature Range (Operating) | -20°C ~ +50°C |
| Wide Dynamic Range (WDR) | WDR 120dB |
| Certifications | IK10 |
| **Camera** | |
| Backlight compensation | Yes |
| Low Speed Shutter | Yes |
| Resolution standard | 2 MP |
| Recording sensor | CMOS |
| Chip size | 1/2,8" |
| Flickerless function | Yes |
| Camera shape | Minsters |
| Signal-to-noise ratio | 48 dB |
| Day/night mode | Automatic,Day,Night |
| White balance | Automatic,Manual |
| Photosensitivity | 0,08 Lux bei F2,2,40 IRE |
| System | True Day&Night |
| Day/night switching | Switchable IR Filter (ICR) |
| **Display** | |
| Image resolution max. | 1920x1080 |
| **DORI** | |
| Watch (62px/m) | 6,8 m |
| Detect (125px/m) | 3 m |
| Identify (250px/m) | 1,5 m |
| Perceiving (25px/m) | 18,6 m |
| **Functions** | |
| Analysis | Intrusion (PID), Manipulation (TD), Motion Detection |
| Audio support | Yes |
| Motion detector | Yes |
| Digital Noise Reduction (DNR) | Yes |
| Multicast | Yes |
| Alarm processing | recording internal storage (SD card),E-Mail,FTP,Boost,HTTP,TCP,UDP,HTTPS,XML,alarm out |

© Copyright VIDEOR E. Hartig GmbH - September 16, 2026 - technical changes reserved

# eneo ISD-52F0023WSA

Continuation of the specifications

| | |
|---|---|
| Audio | 2 Way Audio |
| Browser | Edge: MJPEG setup limited, Google Chrome: MJPEG setup limited, Mozilla: MJPEG setup limited, Safari: MJPEG setup limited |
| Menu languages | Chinese, English, French, German, Japanese, Korean, Russian |
| Password | Administrator and User |
| Internal memory | microSDHC card, microSDXC card |
| **Notes** | |
| Remark | To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necessary,we offer a compatibility check |
| **Interfaces / Inputs/ Outputs** | |
| Alarm inputs | 1 |
| External connections | Alarm output,Alarm input,Audio input/output,RJ-45,12VDC input (DC plug),connection cable approx.55cm |
| **Parts supplied** | |
| Scope of delivery | manual,bag of screws |
| **Lens** | |
| Horizontal angle of view | 135° |
| Vertical angle of view | 75° |
| Iris Control | No |
| Focal length | 2,3 mm |
| MOD (Minimum Object Distance) | 0.3 m |
| Lens Type | Prime lens |
| Zoom Factor (Digital) | 0 |
| **Video** | |
| Image transfer rate max. | 30 fps |
| Resolution (extended) | 1920x1080 (16:9),1440x1080 (4:3),1280x1024 (5:4),1024x768 (4:3),1280x720 (16:9),800x600 (4:3),800x480 (16:9),704x576 (4:3),704x480 (4:3),640x480 (4:3),400x240 (4:3),352x288 (4:3), |
| Data stream types | Quad Streaming |
| Video Compression | H.264, H.264+, H.265, H.265+, M-JPEG |
| **Product labeling:** | |
| Manufacturer order number | 227007 |
| Series | eneo SN-Serie |

## Optional Accessory

| SKU | Name | Description |
|---|---|---|

© Copyright VIDEOR E. Hartig GmbH - September 16, 2026 - technical changes reserved

# eneo ISD-52F0023WSA

Continuation of accessory

| | | |
|---|---|---|
| 218218 | eneo Site Manager | Management Software for eneo IP products |

## Optional Services

| SKU | Name | Description |
|---|---|---|
| 214441 | PAINTING SERVICE basic costs | once per RAL color and delivery lot |
| 229234 | Vorkonfiguration IP-Kamera | Preconfiguration 1x IP camera Function test, FW update |

## Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - September 16, 2026 - technical changes reserved