



# eneo IPD-68M3611P5A

SKU: 227050



1/2,5" Network Dome, Fix, 3840x2160, Day&Night, DOL-WDR, 3,6-11mm, Infrared, Indoor

## Main Features

- 1/2.5" Sony STARVIS CMOS sensor
- Resolution max. 3840x2160, 8 Megapixel
- Motorised varifocal lens 3.6~11mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- VCA video analysis, ONVIF event mapping
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Smart Codec H.265 ROI (Region of interest)
- Quad Smart Streaming: H.265(+), H.264(+), MJPEG
- Slot for Micro SD Card, HTML5 replay
- Power supply PoE or 12VDC
- Wedge adapter included (10° inclination)
- Supports ONVIF Profile S and Profile T

## Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	94x116mm
Weight	0.3 kg
SDK	upon request
Text overlay	available
Color (Housing)	white
Color (dome)	clear

# eneo IPD-68M3611P5A

Continuation of the specifications

Housing type	Inside
Housing material	Plastic
Power consumption	8.5 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Power supply	12VDC, Poe
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
<b>Camera</b>	
Resolution standard	8 MP
Recording sensor	CMOS
Chip size	1/2,5"
Flickerless function	Yes
Camera shape	Minsters
Signal-to-noise ratio	50 dB
Day/night mode	Automatic, Day, Night, night-color mode, extern (Sensor)
White balance	ATW-Indoor, ATW-Outdoor, Manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes
Photosensitivity	0,2 Lux bei F1,5,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	3840x2160
<b>DORI</b>	
Watch (62px/m)	36,7 - 85,7 m
Detect (125px/m)	17,8 - 42,7 m
Identify (250px/m)	8,6 - 21,2 m
Perceiving (25px/m)	91,6 - 214,2 m
<b>Functions</b>	
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Turning range	165 °
Alarm processing	recording internal storage (SD card), E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping
Browser	Edge: MJPEG, Mozilla: MJPEG, Safari: MJPEG
Menu languages	English, French, German, Korean
Password	Administrator and User
Vertical tilt range	+/-60°
Internal memory	microSDHC card, microSDXC card

# eneo IPD-68M3611P5A

Continuation of the specifications

<b>Interfaces / Inputs/ Outputs</b>	
Alarm inputs	0
External connections	RJ-45, 12VDC input (DC plug), connection cable approx. 55cm
Control Interfaces	Ethernet
<b>Parts supplied</b>	
Scope of delivery	manual, bag of screws
<b>Lens</b>	
Horizontal angle of view	84 - 40°
Vertical angle of view	46 - 21°
Focal length	3,6 - 11 mm
MOD (Minimum Object Distance)	0.5 m
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	3
<b>Video</b>	
Image transfer rate max.	30 fps
Resolution (extended)	3840x2160 (16:9), 2592x1520 (16:9), 1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)
Data stream types	Multi-Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
<b>Product labeling:</b>	
Manufacturer order number	227050
Series	eneo LN-Serie

## Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products

## Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

# eneo IPD-68M3611P5A

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

