eneo IPD-65M2713P5A

SKU: 227053



1/2,8" Network Dome, Fix, 2592x1944, Day&Night, DOL-WDR, 2,7-13,5mm, Infrared, Indoor

Main Features

1/2.8" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 2592x1944, 5 Megapixel	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 2,7~13.5mm	Micro SD Card, HTML5 replay
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE or 12VDC
VCA (Video Content Analysis), ONVIF event mapping	Wedge adapter included (10° inclination)
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	94x116mm
Weight	0.3 kg
SDK/API	upon request
Text overlay	available
Color (Housing)	white
Color (dome)	clear

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IPD-65M2713P5A

Continuation of the specifications

Housing type	Inside
Housing material	Plastic
Power consumption	8.5 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Power supply	12VDC, Poe
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	5 MP
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Minsters
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,night-color mode,extern (Sensor)
White balance	ATW-Indoor,ATW-Outdoor,Manual,Fluorescent light,Light bulb,Shade,Clear Sky,Flammes
Photosensitivity	0,05 Lux bei F1,6,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (63px/m)	16,3 - 69,1 m
Detect (125px/m)	7,7 - 34,2 m
Identify (250px/m)	3,6 - 17 m
Perceiving (25px/m)	41,7 - 171,7 m
Functions	
Analysis	Motion Detection
Audio support	No
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Turning range	165 °
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,Boost,TCP,UDP,Onvif Event Mapping

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IPD-65M2713P5A

Continuation of the specifications

Browser	Edge: MJPEG, Mozilla: MJPEG, Safari: MJPEG
Menu languages	English, French, German, Korean
Password	Administrator and User
Vertical tilt range	+/-60°
Internal memory	microSDHC card, microSDXC card
Interfaces / Inputs/ Outputs	
Alarm inputs	0
External connections	micro SD card slot,RJ-45,12VDC power input,connection cable approx.55cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	97° - 29°
Vertical angle of view	54° - 17°
Focal length	2,7 - 13,5 mm
MOD (Minimum Object Distance)	0.5 m
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	4
Video	
Image transfer rate max.	30 fps
Resolution (extended)	2592x1944 (4:3),2592x1520 (16:9),2560x1440 (16:9),1920x1080 (16:9),1600x900 (16:9),1280x720 (16:9),960x540 (16:9),640x360 (16:9),320x180 (16:9)
Data stream types	Multi-Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	227053
Series	eneo LN-Serie

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IPD-65M2713P5A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved