

# eneo IAR-7SE1024MMB

SKU: 228222



Gigabit Switch, 24xPoE 100Mbps 2x RJ45 Gbit, 2xSFP Gbit, 390W, Managed, 19", 1HE

## Main Features

PoE Switch, Rack Montage

Gigabit Uplink Ports: 2xRJ45, 2xSFP

24x 10/100 PoE Ports, IEEE 802.3af/at

Up to 30W per port, Total ≤390W

ESD protection IEC61000-4-5 standard

Managed L2 switch, Built in low-noise fans

Web configuration, Web management

VLAN, PoE management, MAC address table

Port mirroring, password

Status LEDs

Temperature range -10 ° C ~ + 50 ° C

Rack mounting brackets included

## Specifications

General	
Fan	Yes
Management	Yes
Number of PoE ports	24
Design	Rack
Dimensions (WxHxD) (extended)	44,5x442x263mm
Application environment	inside
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	3.8 kg
Type	Layer2 Switch

# eneo IAR-7SE1024MMB

Continuation of the specifications

Power consumption	450 W
Mounting type	19" Rack Installation
PoE Budget (Total)	390 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	100~240VAC
Temperature Range (Operating)	-10°C ~ +50°C
<b>Functions</b>	
Multicast	Yes
<b>Interfaces / Inputs/ Outputs</b>	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	24x 10/100Base-TX, 2x 10/100/1000Base-TX, 2x 10/100/1000T SFP, Console RJ45-RS232, Console RJ45-RS232
<b>Parts supplied</b>	
Scope of delivery	manual,power cord,19" rack mount angle
<b>Network</b>	
VLAN	Yes
Eneo _netzwerkstandards	IEEE 802.1D Spanning Tree Protocol, IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Security	Fast Ring, Password, Port Isolation, Port Speed Setting, Radius Authentication
Internal Switching Capacity (Gbit)	12.8 Gbps
Internal Switching Capacity (MP per second)	9.5 Mpps
<b>Product labeling:</b>	
Manufacturer order number	228222
Series	eneo Switch

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

