eneo IAM-5SE1008MUB

SKU: 228223



Gigabit Switch, 8xPoE 100Mbps, 1x RJ45, 1x SFP 1000Mbps, Unmanaged, Industrial Design

Main Features

- Gigabit PoE switch, DIN Rail
- Gigabit Uplink ports 1xRJ45, 1xSFP
- 8x 10/100 PoE Ports, IEEE 802.3af/at
- Up to 30W per port
- Surge protection IEC61000-4-5 (6KV)
- Status LED: Uplink, PoE, Optical port, Power
- PoE reset button for each port
- CCTV mode allows transmission up to 250m @ 10Mbps
- Temperature range -40° C ~ +75° C

Specifications

General	
Number of PoE ports	8
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	46,5x163x110,5mm
Application environment	inside
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	530 kg
Type	Unmanaged
Mounting type	DIN Rail, Wall
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC

© Copyright VIDEOR E. Hartig GmbH - November 4, 2026 - technical changes reserved

eneo IAM-5SE1008MUB

Continuation of the specifications

Temperature Range (Operating)	-40°C ~ +75°C
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-TX, 1x 10/100/1000T SFP, 8x 10/100Base-TX
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
VLAN	Yes
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX
Internal Switching Capacity (Gbit)	5.6 Gbps
Internal Switching Capacity (MP per second)	4.2 Mpps
Product labeling:	
Manufacturer order number	228223
Series	eneo Switch

Optional Accessory

SKU	Name	Description
218758	eneo SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	eneo SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - November 4, 2026 - technical changes reserved