eneo IAM-5SE1004MUD

SKU: 228224



Switch, Unmanaged, 120W, 4xPoE 1x RJ45, 1x SFP 100Mbps, Industrial Design, -40°C~+75°C

Main Features

Ethernet PoE Switch, DIN Rail	Surge protection IEC61000-4-5 (6KV)
Uplink ports 1xRJ45, 1xSFP	Status LED: Uplink, PoE, Optical port, Power
4x 10/100 PoE Ports,IEEE 802.3af/at	CCTV mode allows transmission up to 250m @ 10Mbps
Up to 30W per port	Temperature range -40° C ~ +75° C

Specifications

General	
Number of PoE ports	4
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	46x110x159mm
Application environment	inside
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	530 kg
Type	Unmanaged
Mounting type	DIN Rail, Wall
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC
Temperature Range (Operating)	-40°C ~ +75°C

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IAM-5SE1004MUD

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Ethernet interface	100Base-TX, 10Base-T
Ports	1x 10/100Base-TX, 1x 100 SFP, 4x 10/100Base-TX
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX
Security	CCTV mode
Internal Switching Capacity (Gbit)	1.5 Gbps
Internal Switching Capacity (MP per second)	0.9 Mpps
Product labeling:	
Manufacturer order number	228224
Series	eneo Switch

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved