



VM-HD19MR

SKU: 229200



19" (48cm) LCD, industrial Monitor, 1280x1024, Protection Glass, Rack Mount, 12V, HDMI

Camera not included

Main Features

Professional 19" (48 cm) LCD monitor	Fast response time 5ms
Built to run 24x7x365 continuously (Industrial Level)	Different video inputs HDMI, VGA, BNC (CVBS)
Including protection glass, Anti-Glare-Display 3H	Audio In- and Output
Extended temperature range -30°C +85°C	Built-in speakers
Maximum resolution 1280x1024 pixels	Supply voltage: 12VDC
LED Back Light	Including 19" mounting frame

Specifications

Applications	Industry
Audio Inputs	1
Viewing Angle Horizontal	178 °
Viewing Angle Vertical	178 °
Screen diagonal (cm)	48 cm
Screen diagonal (inches)	19 1"
Video Inputs	Anti-glare display, Color TFT-LCD, Hard coating (3H)
Comb filter	No
Scope of delivery	manual,power cord,PSU 100~240VAC,IR remote controller,HDMI cable
Menu languages	English

VM-HD19MR

Continuation of the specifications

Video Inputs	HDCP 1.4, HDCP 2.2, HDMI 1.4a
Housing material	Metal
Brightness (typical)	350 cd/m²
Backlight	LED
Contrast ratio (typical)	1000:1
Manufacturer order number	229200
Response time (typical)	5 ms
Aspect ratio	5:4
Series	eneo Monitor
Control Interfaces	no
Video Inputs	2x Composite (FBAS), HDMI, VGA
Refresh rate	60 Hz

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

