



eneo VM-HD19MR

SKU: 229200



19" (48cm) LCD, industrial Monitor, 1280x1024, Protection Glass, Rack Mount, 12V, HDMI

Camera not included

Main Features

Professional 19" (48 cm) LCD monitor

Built to run 24x7x365 continuously (Industrial Level)

Including protection glass, Anti-Glare-Display 3H

Extended temperature range -30°C +85°C

Maximum resolution 1280x1024 pixels

LED Back Light

Fast response time 5ms

Different video inputs HDMI, VGA, BNC (CVBS)

Audio In- and Output

Built-in speakers

Supply voltage: 12VDC

Including 19" mounting frame

Specifications

General	
Applications	Industry
Dimensions (WxHxD) (extended)	482x355x48mm
Fortification	VESA Standard 100x100mm, VESA Standard 75x75mm
Weight	3 kg
Energy efficiency class	E
Color (Housing)	Black
Housing material	Metal
Power consumption	20 W
Power supply	12VDC

eneo VM-HD19MR

Continuation of the specifications

Display	_headline, Anti-glare display, Color TFT-LCD, Hard coating (3H)
Viewing Angle Horizontal	178 °
Viewing Angle Vertical	178 °
Screen diagonal (cm)	48 cm
Screen diagonal (inches)	19 "
Pixel error class	ISO 13406-2, Class 2
Brightness (typical)	250 cd/m ²
Backlight	LED
Contrast ratio (typical)	1000:1
Response time (typical)	5 ms
Aspect ratio	5:4
Refresh rate	60 Hz
Functions	
Comb filter	Yes
Menu languages	English
Notes	
Remark	NDA compliance under Section 889
Interfaces / Inputs/ Outputs	
Audio Inputs	1
Transmission Technology	HDCP 1.4, HDCP 2.2, HDMI 1.4a
Video Outputs	Composite (FBAS)
Video Inputs	2x Composite (FBAS), HDMI, VGA
Parts supplied	
Scope of delivery	manual,power cord,PSU 100~240VAC,IR remote controller,HDMI cable
Video	
Resolution (extended)	800x600,1024x768,1280x1024
Maximum Image Resolution (HV)	1280x1024
Product labeling:	
Manufacturer order number	229200
Series	eneo Monitor

eneo VM-HD19MR

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

