

eneo VM-SD7M

SKU: 229214



Camera not included

7" (17,7cm) LCD Monitor 800x480, LED, HDMI, VGA, Composite

Main Features

Professional 7" (17,7 cm) LCD monitor	Perfect presentation through digital 3D filtering and noise reduction
Industrial design built to run 24x7x365 continuously	Different video inputs HDMI, VGA, Composite
Maximum resolution 800x480 pixels	Supply voltage: 12VDC
LED Back Light	VESA Standard 75x75mm
Fast response time 5ms	Metal cabinet including stand

Specifications

General	
Applications	Industry
Housing material	Metal
Display	_headline, Anti-glare display, Color TFT-LCD
Viewing Angle Horizontal	178 °
Viewing Angle Vertical	178 °
Screen diagonal (cm)	17.7 cm
Screen diagonal (inches)	7 "
Brightness (typical)	250 cd/m²
Backlight	LED
Contrast ratio (typical)	500:1
Response time (typical)	5 ms

eneo VM-SD7M

Continuation of the specifications

Aspect ratio	16:9
Refresh rate	60 Hz
Functions	
Menu languages	English
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
Audio Inputs	1
Transmission Technology	HDCP 1.4, HDCP 2.2, HDMI 1.4a
Control Interfaces	no
Video Inputs	2x Composite (FBAS), HDMI, VGA
Parts supplied	
Scope of delivery	manual,power cord,PSU 100~240VAC,feet,IR remote controller,HDMI cable
Product labeling:	
Manufacturer order number	229214
Series	eneo Monitor

Optional Accessory

SKU	Name	Description
224229	eneo VM-LCDWMB2	Wall bracket for LCD monitors horizontal adjustable, support up to max. 8 kg
241896	Jetrics VM-UMA10	Aluminium gas spring monitor arm for wall mount, LCD Monitors, max. 27" support up to 7 kg max.
241897	Jetrics VM-UTM10	Universal Table Mount for LCD Monitors, up to 45", VESA support up to 13Kg max.
241894	Jetrics VM-UWM10	Universal Wall Mount for LCD Monitors, up to max. 27", VESA support up to 15 kg max.
241898	Jetrics VM-UWM30	Universal Wall Mount for LCD Monitors, up to 43", VESA support up to 20Kg max.

eneo VM-SD7M

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

