



eneo IAM-5SE1008IUA

SKU: 230034



Switch unmanaged, 120W, 8xPoE 1xRJ45 ,1xSFP
Gigabit Industrial Design

Main Features

Ethernet PoE Switch, DIN Rail

Gigabit Uplink ports 1xRJ45, 1xSFP

8x 10/100 PoE Ports,IEEE 802.3af/at

Up to 30W per port, Total ≤240W (optional power supply)

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

CCTV mode allows transmission up to 250m @ 10Mbps

Temperature range -30° C ~ +65° C

Specifications

General	
Number of PoE ports	8
Design	Case
Dimensions (WxHxD) (extended)	44x159x110mm
Application environment	inside
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	500 g
Type	Unmanaged
Mounting type	Desktop
PoE Budget (Total)	240 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC
Temperature Range (Operating)	-30°C ~ +65°C

eneo IAM-5SE1008IUA

Continuation of the specifications

Functions	
Menu languages	English, German
Notes	
Remark	External power supply specification: 100~240VAC,120W,-10°~+55°. To achieve the specified PoE budget (total) value,an appropriate optional power supply unit must be used.
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
PoE Standard	IEEE802.3af, IEEE802.3at
Ports	1x 10/100/1000Base-T, 1x 10/100/1000T SFP, 8x 10/100Base-TX
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
VLAN	Yes
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Security	CCTV mode
Internal Switching Capacity (Gbit)	5.6 Gbps
Internal Switching Capacity (MP per second)	4.0 Mpps
Product labeling:	
Manufacturer order number	230034
Series	eneo Switch

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

