



IAR-7SE2016MMA

SKU: 230114



Gigabit Switch, Managed, 250W 16x PoE, 4x SFP, 1000Mbps, Wall-/Rack mounting, Desktop

Main Features

16-Port Gigabit PoE L2 Managed Ethernet Switch

4x SFP Gigabit Uplink Ports

PoE Standard IEEE 802.3af/at (PSE)

Up to 30W per port, total $\leq 250W$

Fast Ring-Redundant, Reconfiguration <20ms

Surge Immunity 6kV, Standard: IEC6000-4-5

ESD 6 kV Contact Discharge, 8kV Air Discharge, standard: IEC

Web configuration, Web management

VLAN, PoE management, MAC address table

Port mirroring, password protection

Temperature range -10° C ~ +50° C

Rack mounting brackets included

Specifications

Dimensions (HxWxD)	44x442x320mm
Type	Layer2 switch
Series	eneo Switch
Mounting	19" rack, desktop
Blower	yes
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	yes
Ports	16x 10/100/1000Base-T, 4x 1000Mbps SFP, Console RJ45-RS232
PoE ports (number)	16
Management	yes

IAR-7SE2016MMA

Continuation of the specifications

Model	Desktop, Rack Mount
Supply voltage	100~240VAC
Power consumption	270W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	250 W
Operating temperature	-10°C ~ +50°C
Weight	1.9kg
Manufacturer order number	230114

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216567	SFP-0850MM10	SFP Modul, 155Mbps, 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

