



eneo IPD-42M2713PAA

SKU: 230799



1/2,8" Network Dome, Fix, 1920x1080, Day/Night, DOL-WDR 2,7-13,5mm, Infrared, Indoor

Main Features

- 1/2.8" Sony STARVIS CMOS Sensor
- Excellent light sensitivity
- Resolution max. 1920x1080 (Full HD)
- Motorised varifocal lens 2.7~13.5mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- Motion Detection, Privacy Zones, Slow Shutter

- Browser independent (IE, Edge, Safari, Firefox, Chrome)
- Smart Codec H.265 ROI (Region of Interest)
- Supports ONVIF Profile S and Profile T
- Vertical View 90°/270° Modus, H-Flip, Mirror
- Compact Fix Dome Housing (plastic) for indoor
- Power supply PoE or 12VDC

Specifications

| General | |
|-------------------------------|---------------|
| Lighting | Infrared |
| Dimensions (WxHxD) (extended) | 87x113mm |
| Weight | 0.27 kg |
| SDK | upon request |
| Text overlay | available |
| Color (Housing) | white |
| Housing type | Inside |
| Housing material | Plastic (ABS) |
| Power consumption | 7.5 W |

eneo IPD-42M2713PAA

Continuation of the specifications

| | |
|-------------------------------|---|
| Mounting type | Ceiling, Wall |
| ONVIF | ONVIF Profile S, ONVIF Profile T |
| Power over Ethernet | IEEE 802.3af |
| Power supply | 12VDC, Poe |
| Temperature Range (Operating) | -10°C ~ +50°C |
| Wide Dynamic Range (WDR) | D-WDR |
| Camera | |
| Backlight compensation | Yes |
| Low Speed Shutter | Yes |
| Resolution standard | 2 MP |
| Recording sensor | CMOS |
| Chip size | 1/2,8" |
| Flickerless function | Yes |
| Camera shape | Minsters |
| Signal-to-noise ratio | 50 dB |
| Day/night mode | Automatic, Day, Night, extern (Sensor) |
| White balance | Automatic, Outdoor, Light bulb, Fluorescent light, Clear Sky, Shade, Manual |
| Photosensitivity | 0,0008 Lux bei F1,6,40 IRE |
| System | True Day&Night |
| Day/night switching | Switchable IR Filter (ICR) |
| Display | |
| Image resolution max. | 1920x1080 |
| DORI | |
| Watch (62px/m) | 11,8 - 54,5 m |
| Detect (125px/m) | 5,6 - 26,7 m |
| Identify (250px/m) | 2,9 - 13,4 m |
| Perceiving (25px/m) | 30,6 - 135,1 m |
| Functions | |
| Audio support | No |
| Motion detector | Yes |
| Digital Noise Reduction (DNR) | Yes |
| Multicast | Yes |
| Analysis | Manipulation (TD), Motion Detection |
| Alarm processing | E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping |
| Browser | Edge: MJPEG, Mozilla: MJPEG, Safari: MJPEG |
| Menu languages | English, French, German, Korean |
| Password | Administrator and User |
| Notes | |

eneo IPD-42M2713PAA

| | |
|--------|---|
| Remark | NDAA compliance under Section 889, To guarantee you an optimum user experience, we recommend that you only use components of the same brand in a system. If several brands are used in combination, eneo cannot guarantee functionality. If combined use is necessary |
|--------|---|

eneo IPD-42M2713PAA

Continuation of the specifications

| | |
|-------------------------------------|--------------------------------------|
| Interfaces / Inputs/ Outputs | |
| Alarm inputs | 0 |
| External connections | 12VDC input (DC plug),RJ-45 |
| Control Interfaces | Ethernet |
| Parts supplied | |
| Scope of delivery | manual,bag of screws |
| Lens | |
| Horizontal angle of view | 108 - 32° |
| Vertical angle of view | 56 - 18° |
| Focal length | 2,7 - 13,5 mm |
| MOD (Minimum Object Distance) | 0.5 m |
| Lens Type | Varifocal (motorized) |
| Zoom Factor (Digital) | 0 |
| Zoomfactor (optical) | 4 |
| Video | |
| Image transfer rate max. | 30 fps |
| Resolution (extended) | 1920x1080 (16:9),1280x720 (16:9) |
| Data stream types | Multi-Streaming |
| Video Compression | H.264, H.264+, H.265, H.265+, M-JPEG |
| Product labeling: | |
| Manufacturer order number | 230799 |
| Series | eneo AN-Serie |

Optional Services

| SKU | Name | Description |
|--------|----------------------------|--|
| 229234 | Vorkonfiguration IP-Kamera | Preconfiguration 1x IP camera Function test, FW update |

eneo IPD-42M2713PAA

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

