



eneo IPD-52M2713MAA

SKU: 230800



1/2.8" Network Dome, Fix, 1920x1080, Day/Night, DOL-WDR, 2.7-13.5mm, Infrared, IP66

Main Features

- 1/2.8" Sony STARVIS CMOS Sensor
- Excellent light sensitivity
- Resolution max. 1920x1080 (Full HD)
- Motorised varifocal lens 2.7~13.5mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- Motion Detection, Privacy Zones, Slow Shutter

- Browser independent (IE, Edge, Safari, Firefox, Chrome)
- Smart Codec H.265 ROI (Region of Interest)
- Supports ONVIF Profile S and Profile T
- Vertical View 90°/270° Modus, H-Flip, Mirror
- Fix Dome Housing (metal), IP66
- Power supply PoE or 12VDC

Specifications

General	
Lighting	Infrared
Dimensions (WxHxD) (extended)	136x117mm
Weight	0.73 kg
SDK	upon request
Text overlay	available
Color (Housing)	Light Cool Gray 1C
Housing type	Outside
Housing material	Aluminium
Power consumption	8 W

eneo IPD-52M2713MAA

Continuation of the specifications

Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP66
Power supply	12VDC, Poe
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Camera	
Resolution standard	2 MP
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Minsters
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	Automatic,Outdoor,Light bulb,Fluorescent light,Clear Sky,Shade,Manual
Photosensitivity	0,0008 Lux bei F1,6,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	11,9 - 51,5 m
Detect (125px/m)	5,6 - 25,4 m
Identify (250px/m)	2,7 - 12,7 m
Perceiving (25px/m)	30,6 - 127,5 m
Functions	
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	E-Mail,HTTP,FTP,Boost,TCP,UDP,Onvif Event Mapping
Browser	Edge: MJPEG, Mozilla: MJPEG, Safari: MJPEG
Menu languages	English, French, German, Korean
Password	Administrator and User
Internal memory	no
Notes	
Remark	NDAA compliance under Section 889,To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necess

eneo IPD-52M2713MAA

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Alarm inputs	0
External connections	12VDC input (DC plug),RJ-45
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	108 - 32°
Vertical angle of view	56 - 18°
Focal length	2,7 - 13,5 mm
MOD (Minimum Object Distance)	0.5 m
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	4
Video	
Image transfer rate max.	30 fps
Resolution (extended)	1920x1080 (16:9),1280x720 (16:9)
Data stream types	Multi-Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	230800
Series	eneo AN-Serie

Optional Accessory

SKU	Name	Description
232565	eneo AK-12	Camera junction box for wall and ceiling mounting

Optional Services

SKU	Name	Description
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

eneo IPD-52M2713MAA

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

