eneo ICB-62M0550MAA

SKU: 231833



Camera not included

1/2.8" Network Camera, 1920x1080, Day/Night, DOL-WDR, 5.0-50mm, Infrared, IP67

Main Features

1/2.8" Sony STARVIS CMOS Sensor	Browser independent (IE, Edge, Safari, Firefox, Chrome)
Excellent light sensitivity	Smart Codec H.265 ROI (Region of Interest)
Resolution max. 1920x1080 (Full HD)	Supports ONVIF Profile S and Profile T
Motorised varifocal lens 5.0~50mm	Vertical View 90°/270° Modus, H-Flip, Mirror
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE, IP67
Motion Detection, Privacy Zones, Slow Shutter	Integrated connection box including connection board

Specifications

General	
Sunshade canopy	Yes
Integrated wall mount	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	130,50x82,15x265,80mm
Weight	1.3 kg
SDK/API	upon request
Text overlay	available
Color (Housing)	Pantone Cool Gray 1C
Housing type	Outside

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ICB-62M0550MAA

Continuation of the specifications

Housing material	Aluminium
Power consumption	9 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67
Power supply	Poe
Temperature Range (Operating)	-50°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	2 MP
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Bullet
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	Automatic,Outdoor,Light bulb,Fluorescent light,Clear Sky,Shade,Manual
Photosensitivity	0,001 Lux bei F1,6,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (63px/m)	34,3 - 221,5 m
Detect (125px/m)	16,9 - 109,9 m
Identify (250px/m)	7,5 - 54,9 m
Perceiving (25px/m)	86,0 - 549,5 m
Functions	
Analysis	Manipulation (TD), Motion Detection
Audio support	No
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,Boost,TCP,UDP,Onvif Event Mapping,alarm out
Browser	Edge: MJPEG, Mozilla: MJPEG, Safari: MJPEG
Menu languages	English, French, German, Korean

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ICB-62M0550MAA

Continuation of the specifications

Password	Administrator and User
Internal memory	microSDHC card, microSDXC card
Notes	
Remark	NDAA compliance under Section 889,To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necess
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	micro SD card slot,Connection board (LSA,RJ45,audio,I / O alarm & Sabotage contacts)
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	49,9° - 8°
Vertical angle of view	26,7° - 4,5°
Focal length	5 - 50 mm
MOD (Minimum Object Distance)	0.5 m
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	10
Video	
Image transfer rate max.	30 fps
Resolution (extended)	1920x1080 (16:9),1280x720 (16:9)
Data stream types	Multi-Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	231833
Series	eneo AN-Serie

Optional Accessory

SKU	Name	Description
202641	eneo PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ICB-62M0550MAA

Continuation of services

214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211123	PAINTING SERVICE bullet camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved