eneo ISM-65F0028W0A

SKU: 232563



1/2,8" Network Board Camera 2592x1944, Day/Night, WDR, 2,8mm, H.265, PoE, 12VDC

Main Features

1/2.8" Sony STARVIS CMOS Sensor	Browser independent (IE, Edge, Safari, Firefox, Chrome)
Excellent light sensitivity	Object classification (person, car, bike)
Resolution max. 2592x1944 (5MP)	Supports ONVIF Profile S
Lens fixed focal length 2.8mm	Operating temperature -20°C +50°C
WDR (120dB), BLC, 3DNR	Dimensions 50x50x59mm
Tripple Streaming (H.265, H.264, MJPEG)	Power supply PoE or 12VDC

Specifications

General	
Lighting	No
Dimensions (WxHxD) (extended)	siehe Maßzeichnung
Weight	0.26 kg
Text overlay	available
Housing type	without housing
Camera Type	Board Camera
Power consumption	4.2 W
Mounting type	Built-in module
ONVIF	ONVIF Profile S

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISM-65F0028W0A

Continuation of the specifications

Power over Ethernet	IEEE 802.3af
Power supply	12VDC, Poe
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	No
Resolution standard	5 MP
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Printed circuit board
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,Time
White balance	ATW,Manual
Photosensitivity	0,003 Lux bei F1,6
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (63px/m)	26,1 m
Detect (125px/m)	12,3 m
Identify (250px/m)	5,7 m
Perceiving (25px/m)	66,7 m
Functions	
Analysis	Motion Detection
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	alarm out,FTP,E-Mail
Audio	2 Way Audio
Browser	Edge: MJPEG, Google Chrome: Java, Mozilla: MJPEG, MS Internet Explorer 11, Safari: MJPEG
Menu languages	English, German
Password	Administrator and User
Notes	
Remark	NDAA compliance under Section 889,To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necess

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISM-65F0028W0A

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	12VDC power input,Alarm in/output,Audio in/output,RJ-45
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,Connection cable set
Lens	
Horizontal angle of view	105,2°
Vertical angle of view	75,7°
Focal length	2,8 mm
MOD (Minimum Object Distance)	0.5 m
Lens Type	Prime lens
Video	
Image transfer rate max.	30 fps
Resolution (extended)	2592x1944 (4:3),2592x1520 (16:9),2304x1296 (16:9),2048x1536 (4:3),1920x1080 (16:9),1280x1024 (5:4),1024x768 (4:3),1280x720 (16:9),704x576 (4:3),704x480 (4:3),640x480 (4:3),640x360
Data stream types	Multi-Streaming
Video Compression	H.264, H.265
Product labeling:	
Manufacturer order number	232563

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISM-65F0028W0A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved