



# eneo MED-62V2713M0A

SKU: 233015



HD Analogue Dome, Fix, Day&Night 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, IP66, IK10

## Main Features

- ..... 1/2.8" 2.3 Megapixel progressive scan CMOS sensor
- ..... Compact metal housing for outdoor use
- ..... Resolution max. 1920x1080 (Full HD)
- ..... Multisignal: HD-TVI, AHD, CVI, Composite selectable
- ..... Variofocal 2.8~12mm day&night lens
- ..... LSC (Lens shading compensation)

- ..... Removable infrared cut filter
- ..... 3D-DNR noise reduction
- ..... Integral motion detection
- ..... Scratch resistant hard coated bubble
- ..... Easy installation, 3-Axis gimbal

## Specifications

General	
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	108x144,4mm
Illumination range	ca. 30m
Weight	1 kg
Text overlay	Switchable on/off
Color (Housing)	Pantone Cool Gray 1C
Color (dome)	clear
Housing type	Outside

## eneo MED-62V2713M0A

Continuation of the specifications

Housing material	Aluminium
Power consumption	6 W
Mounting type	Ceiling, Wall
Protection	IP66
Power supply	12VDC
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Certifications	IK10
<b>Camera</b>	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS, Sony IMX323
Chip size	1/2,8"
Automatic Electronic Shutter (AES)	1/25 ~ 1/50,000sec
Flickerless function	Yes
Camera shape	Minsters
Manual Electric Shutter (MES)	1-25~1-50,000sec
Signal-to-noise ratio	52 dB
Day/night mode	Yes
White balance	ATW,AWB,Manual,Outdoor,Indoor,AWC
Photosensitivity	0,3 Lux bei F1,6,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	1920x1080
<b>DORI</b>	
Watch (62px/m)	16,6 - 80,5 m
Detect (125px/m)	8,2 - 40,1 m
Identify (250px/m)	3,9 - 20,1 m
Perceiving (25px/m)	44 - 198 m
<b>Functions</b>	
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, Dutch, English, French, German, Italian, Polish, Portuguese, Russian, Spanish, Turkish
Privacy Zone	Areas-ON/OFF switchable
Vertical tilt range	65 °(25 ~ 90°)
<b>Notes</b>	
Remark	NDAA compliance under Section 889
<b>Interfaces / Inputs/ Outputs</b>	
External connections	video (BNC), 12VDC power input, connection cable approx.40cm

## eneo MED-62V2713M0A

Continuation of the specifications

Interface Protocols	UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol)
<b>Parts supplied</b>	
Scope of delivery	manual,Hex L-wrench,screw set,Video sub-out cable,drilling template,bag of screws
<b>Lens</b>	
Horizontal angle of view	95 - 27°
Vertical angle of view	49 - 15°
Focal length	2,7 - 13,5 mm
Aperture Range (F)	F1.6
Lens Type	Varifocal
Zoomfactor (optical)	4
<b>Video</b>	
Resolution (extended)	1920x1080,960x576
Signal Format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, HD-TVI @ 2MP
<b>Product labeling:</b>	
Manufacturer order number	233015
Series	eneo KX-Serie

### Optional Accessory

SKU	Name	Description
230864	eneo AK-11	Camera junction box for wall and ceiling mounting
215644	eneo DOME-WB3	Wall bracket for eneo Dome Cameras MED-62xxxxM0A and IED-62xxxxM0A

### Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

## eneo MED-62V2713M0A

### Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

