



eneo MEB-62V2713P0A

SKU: 233016



HD Analogue Camera Bullet, Day&Night, 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, IP66

Camera not included

Main Features

- 1/2.8" 2.3 Megapixel progressive scan CMOS sensor
- Compact housing for outdoor use
- Resolution max. 1920x1080 (Full HD)
- Multisignal: HD-TVI, AHD, CVI, Composite selectable
- Variofocal 2.8~12mm day&night lens
- LSC (Lens shading compensation)

- Removable infrared cut filter
- 3D-DNR noise reduction
- Digital Wide Dynamic Range (D-WDR)
- Integral motion detection
- 4x High Power LED

Specifications

General	
Sunshade canopy	Yes
Integrated wall mount	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	78,5x78,5x214mm
Illumination range	ca. 30m
Weight	0.52 kg
Text overlay	available
Color (Housing)	Pantone Cool Gray 1C
Housing type	Outside

eneo MEB-62V2713P0A

Continuation of the specifications

Housing material	Aluminium, Plastic
Power consumption	6.5 W
Mounting type	Ceiling, Wall
Protection	IP66
Power supply	12VDC
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Camera	
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Bullet
Signal-to-noise ratio	52 dB
White balance	ATW,AWB,Manual,Outdoor,Indoor,AWC
Photosensitivity	0,3 Lux bei F1,6,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	16,6 - 80,5 m
Detect (125px/m)	8,2 - 40,1 m
Identify (250px/m)	3,9 - 20,1 m
Perceiving (25px/m)	44 - 198 m
Functions	
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, Dutch, English, French, German, Italian, Polish, Portuguese, Russian, Spanish, Turkish
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
Alarm inputs	0
Number of alarm outputs	0
External connections	video (BNC),12VDC power input,connection cable approx.40cm
Interface Protocols	UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol)
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,Easy Bracket,4x wall plugs with screws,video sub-output cable,4x M4x15mm screws,1x Allen wrench

eneo MEB-62V2713P0A

Continuation of the specifications

Lens	
Horizontal angle of view	95 - 27°
Vertical angle of view	49 - 15°
Focal length	2,7 - 13,5 mm
Aperture Range (F)	F1.6
Lens Type	Varifocal
Zoom Factor (Digital)	0
Zoomfactor (optical)	4
Video	
Resolution (extended)	1920x1080,960x576
Signal Format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, HD-TVI @ 2MP
Product labeling:	
Manufacturer order number	233016

Optional Accessory

SKU	Name	Description
230863	eneo AK-10	Camera junction box for wall and ceiling mounting

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211123	PAINTING SERVICE bullet camera	in RAL color
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

eneo MEB-62V2713P0A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

