



VM-HD19MPA

SKU: 233036



19" (48cm) LCD, Industrial Monitor, 1280x1024, HDMI, VGA, Composite, Protection Glass

Main Features

Professional 19" (48 cm) LCD monitor	Fast response time 5ms
Built to run 24x7x365 continuously (Industrial Level)	Different video inputs HDMI, VGA, BNC (CVBS)
Including protection glass, Anti-Glare-Display 3H	Audio In- and Output
Maximum resolution 1280x1024 pixels	Built-in speakers
LED Back Light	Metal cabinet including wall mount

Specifications

Dimensions (HxWxD)	340,6x401,28x49mm
Series	eneo Monitor
Applications	24/7
Resolution Pixels	1280x1024
Housing color	black
Hosuing material	Metal
Backlighting	LED
Screen size (inch)	19"
Screen size (cm)	48 cm
Aspect ratio	5:4
Viewing angle vertical	178°
Viewing angle horizontal	178°

VM-HD19MPA

Continuation of the specifications


Brightness typical	250 cd/m²
Contrast ratio typical	1000:1
Reponse time typical	14 ms
Video inputs (type)	composite (CVBS), HDMI, VGA
Loudspeaker	2
Video outputs	Composite (CVBS)
Audio inputs	1
Serial interfaces	no
Power consumption	25W
Operating temperature	10°C ~ +40°C
Weight	4,1kg
Manufacturer order number	233036
Refresh rate	60 Hz

Optional Accessory

SKU	Name	Description
224229	VM-LCDWMB2	Wall bracket for LCD monitors horizontal adjustable, support up to max. 8 kg
228560	VM-TSHA	Monitor stand high adjustable up to 130mm, for LCD-Monitors, 15-27 Inch, maximum 10Kg

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany



VIDEOR