MEB-55M2812M0A

SKU: 233697
EAN: 4260229840320

1/2.8" HD Camera, Day&Night, 2592x1944, Infrared
2,7-13,5mm, 12VDC, IP67

Main Features

- 1/2.8" CMOS Image Sensor
- Resolution max. 2592x1944
- multi-signal: HD-TVI, AHD, CVI, CVBS
- 2,7-13,5 mm lens with variable focal length (motorized)
- Day/night switching (ICR)
- 2D+3D DNR (Digital Noise Reduction)
- Automatic exposure control (1/30s~1/50,000s)
- Lens shading correction
- IR LED illumination integrated
- For outdoor use degree of protection IP67
- 12VDC power supply, NDAA compliant

Specifications

EAN/GTIN	4260229840320
Dimensions (HxWxD)	83,88x87,4x242mm
Series	eneo COAXIZE, eneo IN-Series
Resolution Pixels	1920x1080, 2560x1440, 2592x1944, 960x540
Resolution Pixels	1920x1080, 2560x1440, 2592x1944, 960x540
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night switch	ICR
Sensitivity	0,05 Lux at F1,2

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved

MEB-55M2812M0A

Continuation of the specifications

Low Speed Shutter	no
Digital Noise Reduction	2D-DNR, 3D-DNR
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	no
Lens Type	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	no
Observe (62 px/m)	24,3 - 104,5 m
Recognize (125 px/m)	11,5 - 52,2 m
Identify (250 px/m)	5,2 - 25,6 m
Detect (25px/m)	62,5 - 260,3 m
Horizontal Angle of View	110,6 - 32,6°
Vertical Angle of View	57,3 - 18,3°
MOD (Mininum Object Distance)	0,8 m
Ilumination	Infrared
Housing	Outdoor
Color (housing)	Pantone P 179-1, RAL9003
Hosuing material	Aluminium
Heater	no
Video outputs	AHD, Composite (CVBS), HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC
Power consumption	6.5W
Vandal proof	no
Operating temperature	-30°C ~ +55°C
Protection rating	IP67
Signal format	AHD @ 2MP, AHD @ 4MP, AHD @ 5MP, Composite (FBAS), CVI @ 2MP, CVI @ 4MP, HD-TVI @ 2MP, HD-TVI @ 4MP, HD-TVI @ 5MP
Camera type	Bullet
Frame rate	20fps @ 2592x1944p, 25/30fps @ 1920x1080p, 25/30fps @ 2560x1440p
Aperture range (F)	F1.8~F3.3
Illumination range	approx. 35m
Weight	745g
Manufacturer order number	233697

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved

MEB-55M2812M0A

Continuation of the specifications

Optional Accessory

SKU	Name	Description
233754	AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	AK-21	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
235339	AK-24	Dual camera connection box for Bullet or Fix Dome IN-Series cameras
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
235257	PM-21	Pole mounting adapter for camera connection box AK-20 and AK-21
235340	WB-24	Wall bracket for Dual camera connection box AK-24

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

VIDEOR

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved