



# eneo MED-65M2812M0A

SKU: 233706

EAN: 4260229840337



1/2,8" HD Dome, Fix, Day&Night, 2592x1944, Infrared  
2,7-13,5mm, 12VDC, IP67

## Main Features

1/2.8" CMOS Image Sensor

Resolution max. 2592x1944

multi-signal: HD-TVI, AHD, CVI, CVBS

2,7-13,5 mm lens with variable focal length (motorized)

Day/night switching (ICR)

2D+3D DNR (Digital Noise Reduction)

Automatic exposure control (1/30s~1/50,000s)

Lens shading correction

IR LED illumination integrated

For outdoor use degree of protection IP67

12VDC power supply, NDAA compliant

## Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	148.0x109.0mm
Illumination range	ca. 35m
Text overlay	available
Color (Housing)	RAL9003,Pantone P 179-1
Housing type	Outside
Housing material	Aluminium

# eneo MED-65M2812M0A

Continuation of the specifications

Power consumption	6.5 W
Mounting type	Ceiling, Wall
Protection	IP67
Power supply	12VDC
Temperature Range (Operating)	-30°C ~ +55°C
Wide Dynamic Range (WDR)	WDR 120dB
Certifications	IK10
Zoomfactor (optical)	4
<b>Camera</b>	
Recording sensor	CMOS
Chip size	1/2,8"
Camera shape	Minsters
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night
White balance	Manual,Automatic
Photosensitivity	0,05 Lux bei F1,2
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	2592x1944
<b>DORI</b>	
Watch (62px/m)	24,3 - 104,5 m
Detect (125px/m)	11,5 - 52,2 m
Identify (250px/m)	5,2 - 25,6 m
Perceiving (25px/m)	62,5 - 260,3 m
<b>Functions</b>	
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, French, Italian, Japanese, Polish, Portuguese, Russian, Spanish
Privacy Zone	Areas-ON/OFF switchable
<b>Notes</b>	
Remark	NDAA compliance under Section 889
<b>Interfaces / Inputs/ Outputs</b>	
Alarm inputs	0
Number of alarm outputs	0
External connections	12VDC power input,video (BNC)
Control Interfaces	Coaxitron (HD Protocol)
<b>Parts supplied</b>	
Scope of delivery	manual,bag of screws
<b>Lens</b>	
Horizontal angle of view	110,6 - 32,6°
Vertical angle of view	57,3 - 18,3°

## eneo MED-65M2812M0A

Continuation of the specifications

Focal length	2,7 - 13,5 mm
Aperture Range (F)	F1.8~F3.3
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
<b>Video</b>	
Resolution (extended)	2592x1944,2560x1440,1920x1080,960x540
Signal Format	AHD @ 2MP, AHD @ 4MP, AHD @ 5MP, Composite (FBAS), CVI @ 2MP, CVI @ 4MP, HD-TVI @ 2MP, HD-TVI @ 4MP, HD-TVI @ 5MP
<b>Product labeling:</b>	
EAN/GTIN	4260229840337
Manufacturer order number	233706
Series	eneo IN-Serie,eneo COAXIZE

### Optional Accessory

SKU	Name	Description
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
235525	eneo AK-25	Camera junction box for ceiling pipe DOME-CH6 and wall bracket DOME-WB6
235526	eneo AK-26	Camera junction box for wall- and ceiling mount Fix dome cameras IN-Serie
236663	eneo DOME-WB8	Wall bracket for PTZ dome INP-54M2812M0A and IND-5 Dome Series
237253	eneo IN-Dome-S2	Sunshield for eneo IN-series Fix Dome IND-62xx, IND-65xx, IND-68xx
239856	eneo IND-FMH2	Ceiling installation adapter with white cover ring for dome cameras IN-Series

### Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

## eneo MED-65M2812M0A

### Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

