



eneo IND-42M2808M0A

SKU: 233796

EAN: 4260229840191



Mini Network Dome Camera Fix, 1920x1080, Day/Night, WDR, AI 2,8-8mm, IR, 12VDC, PoE, IP66, IK10

Main Features

1/2.8" Sony STARVIS CMOS sensor, 2 MP/60fps

AI analysis functions including object classification

WDR 120dB, 3D-DNR Noise Reduction

Motorized varifocal lens 2.8-8mm

Smart Codec H.265/H.264, multi-streaming

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Supports ONVIF profiles S/T/G/M

Multilingual menu navigation (OSD)

Local storage via Micro SD card

Supports audio and external alarm input and output

NDA compliance

IR LED illumination, IP66 and vandal proof IK10

Specifications

General	
Heating	No
Vandalism-resistant	Yes
Audio compression	G.711
Lighting	Infrared
Dimensions (WxHxD) (extended)	115x91,6mm
Illumination range	Approx. 20m
ESC	1/5 ~ 1/20.000sec.
Weight	0.48 kg
SDK	upon request

eneo IND-42M2808M0A

Continuation of the specifications

Text overlay	Switchable on/off
Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request
Color (dome)	clear
Housing type	Outside
Housing material	Aluminium
Camera Type	Domecamera
Power consumption	7 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP66
Power supply	12VDC, Poe
Temperature Range (Operating)	-35°C ~ +60°C,@ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	120dB, D-WDR
Certifications	IK10
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	2 MP
Recording sensor	CMOS, Sony IMX307
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Minsters
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Signal-to-noise ratio	36 dB
Day/night mode	Automatic,Day,Night,Image,Time
White balance	Automatic,Manual
Photosensitivity	0,002 Lux bei F1,2
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	16,8 - 39,3 m
Detect (125px/m)	7,4 - 19,3 m
Identify (250px/m)	2,7 - 9,7 m
Perceiving (25px/m)	45,7 - 99,5 m
Functions	
Audio support	Yes

eneo IND-42M2808M0A

Continuation of the specifications

Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Turning range	350 °
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,alarm out,Cloud Upload
Audio	2 Way Audio
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
Vertical tilt range	0~ +80°
Internal memory	microSD card slot
Notes	
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	RJ-45,Alarm in/output,Audio input/output,12VDC input (DC plug),connection cable approx.45cm,micro SD card slot 256 GB
Ethernet interface	100Base-TX, 10Base-T
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,4 wall plugs with screws,1 Torx wrench,waterproof cover for RJ45 connector
Network	
Network Protocols	DDNS, DHCP, DNA, FTP, HTTP, HTTPS, NTP, RTP, RTSP, SMTP, TCP-IP, UPnP
Lens	
Horizontal angle of view	107 - 45°
Vertical angle of view	55 - 26°
Focal length	2,8 - 8 mm
Aperture Range (F)	F1,2
MOD (Minimum Object Distance)	0.8 m
Lens Type	Varifocal (motorized)
Zoomfactor (optical)	2.8
Video	
Image transfer rate max.	60 fps

eneo IND-42M2808M0A

Continuation of the specifications

Resolution (extended)	1920x1080 (16:9),1280x960 (4:3),1280x720 (16:9),640x480 (4:3),320x240 (4:3)
Picture size	16:9, 4:3
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
EAN/GTIN	4260229840191
Manufacturer order number	233796
Series	eneo IN-Serie

Optional Accessory

SKU	Name	Description
234753	eneo AK-22	Camera junction box for wall and ceiling mount, Mini Dome IND-42M2808M0A
234754	eneo AK-23	Camera connection box for Mini Dome IND-42M2808M0A for holder Dome-WB6/Dome-CH6
234757	eneo DOME-WB7	Wall bracket for Mini Dome IND-42M2808M0A
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

eneo IND-42M2808M0A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

