



# eneo IND-62M2812M0A

SKU: 233819

EAN: 4260229840177



Network Dome Camera Fix, 1920x1080, Day/Night, WDR, AI 2,8-12mm, IR, 12VDC, PoE, IP67, IK10

## Main Features

1/2.8" Sony STARVIS CMOS sensor, 2 MP/60fps

AI analysis functions including object classification

WDR 120dB, 3D-DNR Noise Reduction

Motorized varifocal lens 2.8-12mm

Smart Codec H.265/H.264, multi-streaming

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Supports ONVIF profiles S/T/G/M

Multilingual menu navigation (OSD)

Local storage via Micro SD card

Supports audio and external alarm input and output

NDA compliance

IR LED illumination, IP67 and vandal proof IK10

## Specifications

General	
Heating	No
Vandalism-resistant	Yes
Audio compression	G.711
Lighting	Infrared
Dimensions (WxHxD) (extended)	109x148,7mm
Illumination range	Approx. 30 m
ESC	1/5 ~ 1/20.000sec.
Weight	1 kg
SDK	upon request

# eneo IND-62M2812M0A

Continuation of the specifications

Text overlay	Switchable on/off
Color (Housing)	RAL9003,Other colors available upon request
Color (dome)	clear
Housing type	Outside
Housing material	Aluminium
Camera Type	Domecamera
Power consumption	7 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67, NEMA 4X
Power supply	12VDC, Poe
Temperature Range (Operating)	-35°C ~ +55°C,@ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	D-WDR
Certifications	IK10
<b>Camera</b>	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	2 MP
Recording sensor	CMOS, Sony IMX307
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Minsters
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Signal-to-noise ratio	36 dB
Day/night mode	Automatic,Day,Night,Image,Time
White balance	Automatic,Manual
Photosensitivity	0,002 Lux bei F1,6
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	1920x1080
<b>DORI</b>	
Watch (62px/m)	13,4 - 52,7 m
Detect (125px/m)	6,3 - 26 m
Identify (250px/m)	3,1 - 13 m
Perceiving (25px/m)	34,1 - 130,8 m
<b>Functions</b>	

## eneo IND-62M2812M0A

Analysis	Abandoned and Removed Objects (SOD), Attendance (FA), Crowds (CD), Enter Region, Face Attributes (AD), Face Capture (FD), Face Recognition (FR), Heat Map (HM), Intrusion, Intrusion (PID), Leave Region, License plate recognition (LPD), License plate recognition (LPR), Line crossing (LCD), Manipulation (TD), Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD)
----------	---

# eneo IND-62M2812M0A

Continuation of the specifications

Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Turning range	350 °
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,alarm out,Cloud Upload
Audio	2 Way Audio
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
Vertical tilt range	0~ +75°
Internal memory	microSD card slot
<b>Notes</b>	
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
<b>Interfaces / Inputs/ Outputs</b>	
Alarm inputs	1
External connections	RJ-45,Alarm in/output,Audio input/output,12VDC input (DC plug),connection cable approx.45cm,micro SD card slot 256 GB
Ethernet interface	100Base-TX, 10Base-T
Control Interfaces	Ethernet
<b>Parts supplied</b>	
Scope of delivery	Anschluss Quick installation guide,drilling template,4 wall plugs with screws,1 Torx wrench,waterproof cover for RJ45 connector
<b>Network</b>	
Network Protocols	DDNS, DHCP, DNA, FTP, HTTP, HTTPS, NTP, RTP, RTSP, SMTP, TCP-IP, UPnP
<b>Lens</b>	
Horizontal angle of view	101 - 33°
Vertical angle of view	52 - 18°
Focal length	2,8 - 12 mm
Aperture Range (F)	F1.6
MOD (Minimum Object Distance)	1.2 m
Lens Type	Varifocal (motorized)
Zoomfactor (optical)	4
<b>Video</b>	

# eneo IND-62M2812M0A

Continuation of the specifications

Image transfer rate max.	60 fps
Resolution (extended)	1920x1080 (16:9), 1280x960 (4:3), 1280x720 (16:9), 640x480 (4:3), 320x240 (4:3)
Picture size	16:9, 4:3
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
<b>Product labeling:</b>	
EAN/GTIN	4260229840177
Manufacturer order number	233819
Series	eneo IN-Serie

## Optional Accessory

SKU	Name	Description
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
235525	eneo AK-25	Camera junction box for ceiling pipe DOME-CH6 and wall bracket DOME-WB6
235526	eneo AK-26	Camera junction box for wall- and ceiling mount Fix dome cameras IN-Series
236663	eneo DOME-WB8	Wall bracket for PTZ dome INP-54M2812M0A and IND-5 Dome Series
237253	eneo IN-Dome-S2	Sunshield for eneo IN-series Fix Dome IND-62xx, IND-65xx, IND-68xx
239856	eneo IND-FMH2	Ceiling installation adapter with white cover ring for dome cameras IN-Series
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products

## Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

# eneo IND-62M2812M0A

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

