



# eneo INP-75A0033MIA

SKU: 234751

EAN: 4260229840160



Network Dome, PTZ, 33x, 2952x1944, Day & Night, WDR, AI, Alarm, Audio, 24VAC/12VDC, PoE, IP66

## Main Features

- 1/2.7" CMOS sensor, maximum resolution 5 MP/30fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR Noise Reduction
- Motorized autofocus zoom lens 33x 4.3-142mm
- Smart Codec H.265/H.264, multi-streaming
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Supports ONVIF Profile S and Profile T
- Local storage via Micro SD card
- Audio input and output
- IR LED illumination, IP66
- Wall bracket included

## Specifications

General	
Heating	No
Lighting	Infrared
Dimensions (WxHxD) (extended)	206,4×351,8mm
Weight	3.7 kg
Color (Housing)	RAL9003,Pantone P 179-1,black
Housing type	Outside
Housing material	Aluminium
Camera Type	Face, People counting, Retail Intelligence
Power consumption	25.5 W

# eneo INP-75A0033MIA

Continuation of the specifications

Mounting type	Wall
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3at
Protection	IP66
Power supply	12VDC, PoE+
Temperature Range (Operating)	-30°C ~ +60°C, @ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	WDR 120dB
<b>Camera</b>	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	5 MP
Recording sensor	CMOS
Chip size	1/2,7"
Flickerless function	Yes
Camera shape	PTZ
Day/night mode	Automatic, Day, Night, Image, Time
White balance	Automatic, Manual
Photosensitivity	0,003 Lux bei F1,6
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	2592x1944
<b>DORI</b>	
Watch (62px/m)	42,5 - 1041 m
Detect (125px/m)	20,5 - 515 m
Identify (250px/m)	10 - 258 m
Perceiving (25px/m)	106 - 2596 m
<b>Functions</b>	
Analysis	Face Capture (FD), Face Recognition (FR), Heat Map (HM), Line crossing (LCD), Manipulation (TD)
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Turning range	360
Alarm processing	recording internal storage (SD card), E-Mail, FTP, Cloud Upload
Audio	2 Way Audio
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish

# eneo INP-75A0033MIA

Continuation of the specifications

Password	Administrator and User
Tours	1 selectable tour
Speed (manual control)	200 °/sec
Speed (Target Approach)	200 °/sec
Internal memory	microSD card slot
<b>Notes</b>	
Remark	The face recognition functions are only available with an inserted SD card or in conjunction with a recorder of the eneo IN series.,To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If sev
<b>Interfaces / Inputs/ Outputs</b>	
Alarm inputs	0
External connections	RJ-45,Audio input/output,12VDC input (DC plug),connection cable approx.45cm,micro SD card slot 256 GB
Control Interfaces	Ethernet
<b>Parts supplied</b>	
Scope of delivery	manual,wall bracket,bag of screws
<b>Lens</b>	
Horizontal angle of view	55 - 2,3°
Vertical angle of view	41,6 - 1,7°
Focal length	4,3 - 142 mm
MOD (Minimum Object Distance)	0 m
Lens Type	Auto Focus Zoom
Zoomfactor (optical)	33
<b>Video</b>	
Image transfer rate max.	30 fps
Resolution (extended)	2592x1944 (4:3),2592x1520 (16:9),2304x1296 (16:9),1920x1080 (16:9),1280x960 (4:3),640x480 (4:3),320x240 (4:3)
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
<b>Product labeling:</b>	
EAN/GTIN	4260229840160
Manufacturer order number	234751
Series	eneo IN-Serie

# eneo INP-75A0033MIA

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

