eneo ISM-32F0036M00

SKU: 234978



1/2,8" Mini Network Modul, 1920x1080, Day&Night, 3DNR, 3,6mm, 12VDC, PoE, Indoor

Main Features

- Sony STARVIS 2MP Image Sensor
- Resolution max. 1920x1080 (Full HD)
- Video Compression Format: H.264/MJPEG
- Motion Detection
- Built in SD micro slot
- Low Speed Shutter
- 2DNR, 3DNR and WDR support
- PoE Cable
- Lens 3.6mm (further lenses upon request)
- Power Supply 12VDC (1.8W) or PoE (IEEE802.3af)
- Operation Temperature -10°C - +50°C

Specifications

General	
Lighting	No
Dimensions (WxHxD) (extended)	35x35mm
Weight	0.2 kg
Text overlay	available
Color (Housing)	black
Housing type	Inside
Housing material	Metal
Camera Type	Board Camera
Power consumption	1.8 W

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISM-32F0036M00

Continuation of the specifications

Mounting type	Ceiling, Wall
Power over Ethernet	IEEE 802.3af
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	WDR 100dB
Certifications	IK08
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	2 MP
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Module
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night
White balance	Indoor,Outdoor,User defined,Push
Photosensitivity	0,1 Lux bei F2,5,30 IRE
System	Electronic Day&Night
Day/night switching	Electronic
Display	
Image resolution max.	1920x1080
DORI	
Watch (63px/m)	22 m
Detect (125px/m)	9,9 m
Identify (250px/m)	3,6 m
Perceiving (25px/m)	56,6 m
Functions	
Analysis	Motion Detection
Audio support	No
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Alarm processing	FTP
Browser	Edge: MJPEG, Mozilla: MJPEG, MS Internet Explorer from Vers. 9.0 or higher, Safari: MJPEG
Menu languages	English
Password	Administrator and User
Internal memory	microSD card slot
Notes	

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISM-32F0036M00

Remark	To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If several brands are used in combination,eneo cannot guarantee functionality. If combined use is necessary,we offer a compatibility check

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo ISM-32F0036M00

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Alarm inputs	0
External connections	RJ-45,connection cable approx.15cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws,mounting bracket
Lens	
Horizontal angle of view	92°
Vertical angle of view	49°
Iris Control	No
Focal length	3,6 mm
Zoom Factor (Digital)	0
Video	
Image transfer rate max.	30 fps
Resolution (extended)	1920x1080 (16:9),1280x720 (16:9),800x600 (4:3),704x480 (4:3),640x480 (4:3),320x240 (4:3)
Data stream types	2x H.264,1x MJPEG simultan
Video Compression	H.264, M-JPEG
Product labeling:	
Manufacturer order number	234978

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

VIDEOR

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved