eneo INB-55M2713M0A

SKU: 234993
EAN: 4260229840078



Network Camera Bullet, 2592x1944, Day/Night, WDR, AI, 2,7-13,5mm, IR, 12V, PoE, IP67

Main Features

1/2.7" CMOS sensor,5 MP/30fps	Supports ONVIF profiles S/T/G/M
AI analysis functions including object classification	Multilingual menu navigation (OSD)
WDR 120dB, 3D-DNR Noise Reduction	Local storage via Micro SD card
Motorized varifocal lens 2.7-13.5mm	Supports audio and external alarm input and output
Smart Codec H.265/H.264, multi-streaming	NDAA compliance
Browser independent (IE, Edge, Safari, Firefox, Chrome)	IR LED illumination, IP67

Specifications

General	
Heating	No
Sunshade canopy	Yes
Integrated wall mount	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	83,88x87,4x242mm
Illumination range	Approx. 45m
ESC	1/5 ~ 1/20.000sec.
Weight	0.68 kg
SDK/API	upon request

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo INB-55M2713M0A

Continuation of the specifications

Text overlay	Switchable on/off
Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request
Housing type	Outside
Housing material	Aluminium
Camera Type	Bullet Camera
Power consumption	4.5 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67, NEMA 4X
Power supply	12VDC, Poe
Temperature Range (Operating)	-35°C ~ +55°C,@ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	5 MP
Recording sensor	CMOS, OmniVision OS05A20
Chip size	1/2,7"
Flickerless function	Yes
Camera shape	Bullet
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Signal-to-noise ratio	39 dB
Day/night mode	Automatic,Day,Night,Image,Time
White balance	Automatic,Manual
Photosensitivity	0,003 Lux bei F1,6
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (63px/m)	19,2 - 74,5 m
Detect (125px/m)	9 - 36,3 m
Identify (250px/m)	4,1 - 18,2 m
Perceiving (25px/m)	49,8 - 185 m
Functions	

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo INB-55M2713M0A

Analysis	Image rotation for cameras mounted at a 90° angle, Abandoned and Removed Objects (SOD), Attendance (FA), Crowds (CD), Enter Region, Face Attributes (AD), Face Capture (FD), Face Recognition (FR), Heat Map (HM), Intrusion, Intrusion (PID), Leave Region, License plate recognition (LPD), License plate recognition (LPR), Line crossing (LCD), Manipulation (TD), Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD)

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo INB-55M2713M0A

Continuation of the specifications

Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,alarm out,Cloud Upload
Audio	2 Way Audio
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
Internal memory	microSD card slot
Notes	
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	RJ-45,Alarm in/output,Audio input/output,12VDC input (DC plug),connection cable approx.30cm,micro SD card slot 256 GB
Ethernet interface	100Base-TX, 10Base-T
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,3x wall plugs with screws,2x Allen wrenches,waterproof cover for RJ45 connector
Network	
Security	Complicated password, IEEE 802.1X-Authentication (available from firmware version 8.2.4.1), IP address filtering, Password
Network Protocols	DDNS, DHCP, DNA, FTP, HTTP, HTTPS, IEE 802.1, NTP, RTP, RTSP, SMTP, TCP-IP, UPnP
Lens	
Horizontal angle of view	102° - 31°
Vertical angle of view	73° - 23°
Focal length	2,7 - 13,5 mm
Aperture Range (F)	F1.6
MOD (Minimum Object Distance)	0.3 m
Lens Type	Varifocal (motorized)
Zoomfactor (optical)	4

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo INB-55M2713M0A

Continuation of the specifications

Video	
Image transfer rate max.	30 fps
Resolution (extended)	2592x1944 (4:3),2592x1520 (16:9),2304x1296 (16:9),1920x1080 (16:9),1280x960 (4:3),640x480 (4:3),320x240 (4:3)
Picture size	16:9, 4:3
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
EAN/GTIN	4260229840078
Manufacturer order number	234993
Series	eneo IN-Serie

Optional Accessory

SKU	Name	Description
233754	eneo AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	eneo AK-21	Camera connection box for Wall and ceiling mounting, Bullet and Dome Cameras IN series
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
245314	eneo AK-30	Camera junction box for wall- and ceiling mount fix turret dome and bullet cameras IN-Serie
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
235257	eneo PM-21	Pole mounting adapter, steel for camera connection box AK-20, AK-21 and wall mount WB-24
245272	eneo PM-21	Pole mounting adapter V2A stainless steel, for camera connection box AK-20, AK-21 and wall mount WB-24
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211123	PAINTING SERVICE bullet camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo INB-55M2713M0A

Continuation of services

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved