



eneo IND-55M2812MTA

SKU: 236666

EAN: 4260229840566



Network Dome Camera Fix, Turret, 2880x1620, Day/Night, WDR, AI, 2,8-12mm, IR, White Light, 12VDC, PoE, IP67

Main Features

- 1/2.7" SmartSens CMOS sensor,
- Maximum resolution 2880x1620 pixels, 30fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR noise reduction
- Motorised varifocal lens 2.8-12mm
- Smart Codec H.265/H.264, multi-streaming

- Browser independent (Edge, Safari, Firefox, Chrome)
- Supports ONVIF profiles S/T/G/M
- Local storage via Micro SD card
- Supports audio and external alarm input and output
- NDA compliance
- IR and white light LED illumination, IP67

Specifications

General	
Heating	No
Lighting	Infrared, White
Dimensions (WxHxD) (extended)	135x126,5mm
Illumination range	approx. 30m IR approx. 25m white light
ESC	1/5 ~ 1/20.000sec.
Weight	0.82 kg
SDK	upon request
Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request

eneo IND-55M2812MTA

Continuation of the specifications

Housing type	Outside
Housing material	Aluminium
Camera Type	Domecamera
Power consumption	8.6 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67, NEMA 4X
Power supply	12VDC, Poe
Temperature Range (Operating)	-35°C ~ +60°C, @ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	5 MP
Recording sensor	CMOS, Sensor SC500AI
Chip size	1/2,7"
Flickerless function	Yes
Camera shape	Minsters
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Signal-to-noise ratio	39 dB
Day/night mode	Automatic, Day, Night, Image, Time
White balance	Automatic, Manual
Photosensitivity	0,002 Lux bei F1,0
System	24h Color
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2880x1620
DORI	
Watch (62px/m)	16,6 - 74,5 m
Detect (125px/m)	7,8 - 36,9 m
Identify (250px/m)	3,7 - 18,3 m
Perceiving (25px/m)	42,8 - 185,1 m
Functions	
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes

eneo IND-55M2812MTA

Analysis

Abandoned and Removed Objects (SOD), Attendance (FA), Crowds (CD), Enter Region, Face Capture (FD), Face Recognition (FR), Heat Map (HM), Intrusion, Intrusion (PID), Leave Region, License plate recognition (LPD), License plate recognition (LPR), Line crossing (LCD), Manipulation (TD), Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD)

eneo IND-55M2812MTA

Continuation of the specifications

Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,Red & blue flashing lights,alarm out,Cloud Upload,Siren
Audio	93±3dB max., Built-in microphone, Built-in speaker
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
Internal memory	microSD card slot
Notes	
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	RJ-45,12VDC input (DC plug),connection cable approx.30cm,micro SD card slot 256 GB
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,3x wall plugs with screws,1x Allen wrench,1x waterproof cover for RJ45 connector
Network	
Network Protocols	DDNS, DHCP, DNS, FTP, HTTP, HTTPS, IEE 802.1, NTP, RTP, RTSP, SMTP, TCP-IP, UPnP
Lens	
Horizontal angle of view	113 - 35°
Vertical angle of view	59 - 20°
Focal length	2,8 - 12 mm
Aperture Range (F)	F1,2
MOD (Minimum Object Distance)	1.5 m
Lens Type	Varifocal (motorized)
Zoomfactor (optical)	4
Video	
Image transfer rate max.	30 fps
Resolution (extended)	2880x1620 (16:9) @ H.265,2592x1520 (16:9) @ H.264,2304x1296 (16:9),1920x1080 (16:9),1280x960 (4:3),1280x720 (16:9),640x480 (4:3),320x240 (4:3)
Picture size	16:9, 4:3
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG

eneo IND-55M2812MTA

Continuation of the specifications

Product labeling:	
EAN/GTIN	4260229840566
Manufacturer order number	236666
Series	eneo IN-Serie

Optional Accessory

SKU	Name	Description
233775	eneo AK-21	Camera connection box for Wall and ceiling mounting, Bullet and Dome Cameras IN series
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
245314	eneo AK-30	Camera junction box for wall- and ceiling mount fix turret dome and bullet cameras IN-Serie
236663	eneo DOME-WB8	Wall bracket for PTZ dome INP-54M2812M0A and IND-5 Dome Series
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

eneo IND-55M2812MTA

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

