eneo IAD-5SG1004MUC

SKU: 237369



Camera not included

Gigabit Switch, Unmanaged, 60W, 4x PoE, 1x RJ45, 1x SFP, 10/100/1000 Mbps, Desktop

Main Features

Gigabit PoE switch, desktop application	Temperature range (operation) -5°C~45°C
4x 10/100/1000 PoE+ ports, IEEE 802.3af/at	CCTV mode enables transmission up to 250m @10Mbps
Gigabit uplink ports: 1x RJ45, 1x SFP	CCTV mode supports PoE watchdog function
Up to 30W per port, total ≤60W.	Plug and Play, no settings required
Overvoltage protection IEC61000-4-5 (6KV).	Metal housing

Specifications

General	
Number of PoE ports	4
Design	Desktop
Dimensions (WxHxD) (extended)	27x135x86mm
Application environment	inside
ESD protection	IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6
Weight	300 kg
Type	Unmanaged
Power consumption	65 W
Mounting type	Desktop
PoE Budget (Total)	60 W

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IAD-5SG1004MUC

Continuation of the specifications

Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC
Temperature Range (Operating)	-5°C ~ +45°C
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-T, 1x 1000Base-X SFP, 4x 10/100/1000Base-T (PoE)
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Security	CCTV mode
Internal Switching Capacity (Gbit)	12 Gbps
Internal Switching Capacity (MP per second)	8.9 Mpps
Product labeling:	
Manufacturer order number	237369

Optional Accessory

SKU	Name	Description
218758	eneo SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	eneo SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

VIDEOR

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved