

# eneo IAM-5SE1004IUP

SKU: 237908



Gigabit Switch, Unmanaged 120W, 4x PoE, Industrial Design -20°C~+65°C, PD port

## Main Features

- Gigabit PoE Switch, DIN Rail
- 4x 10/100/1000 PoE ports, IEEE 802.3af/at/bt
- Maximum 90W power budget
- 1 x SFP Gigabit uplink port
- 1 x RJ45 Gigabit uplink port, PD-capable (90W PoE input)

- CCTV mode, extended transmission distance
- 1 x output relay
- Overvoltage protection IEC61000-4-5 (6KV)
- Temperature range -20°C ~ +65°C

## Specifications

General	
Number of PoE ports	4
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	44x110x160mm
Application environment	inside
ESD protection	IEC61000-4-2
Weight	540 kg
Type	Unmanaged
Power consumption	130 W
Mounting type	DIN Rail
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt

# eneo IAM-5SE1004IUP

Continuation of the specifications

Power supply	48-56VDC, Poe
Temperature Range (Operating)	-40°C ~ +65°C
<b>Notes</b>	
Remark	Power supply unit is not included in the scope of delivery, To achieve the specified PoE budget (total value, please use suitable power supplies or PoE injector. PoE budget: 90W max. for a single PoE port; 75W max. for all PoE ports when supplied via PD port
<b>Interfaces / Inputs/ Outputs</b>	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-T (PoE-PD), 1x 1000Base-X SFP, 4x 10/100/1000Base-T
<b>Parts supplied</b>	
Scope of delivery	manual, power cord, Mounting Bracket
<b>Network</b>	
Eneo _netzwerkstandards	IEEE 802.1D Spanning Tree Protocol, IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Internal Switching Capacity (Gbit)	12 Gbps
Internal Switching Capacity (MP per second)	8.9 Mpps
<b>Product labeling:</b>	
Manufacturer order number	237908
Series	eneo Switch

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

