



# eneo IND-58F0002MTDA

SKU: 238644

EAN: 4260229840726



Network Dome Camera Fix, Turret, Panorama 180°, 2x 5120x1440, Day/Night, DWDR, AI, 2x 2,8mm, IR, White Light, 12VDC, PoE, IP67

## Main Features

- Multisensor 2x 1/2.7' CMOS sensor, panorama
- Maximum resolution 5120x1440 pixels each, 15fps
- Panorama ultra wide-angle camera 180° HFoV, 32:9
- AI analysis functions including object classification
- WDR, BLC, HLC and 3D-DNR noise reduction
- Lenses with 2.8mm fixed focal length

- Smart Codec H.265/H.264, dual streaming
- Browser-independent (Edge, Safari, Firefox, Chrome)
- Supports ONVIF profiles S/T/G/M and audio
- Local storage via micro SD card
- NDA compliance
- Integrated IR and white light LED illumination, IP67

## Specifications

General	
Heating	No
Lighting	Infrared, White
Dimensions (WxHxD) (extended)	112,4x135mm
Illumination range	Approx. 30 m   Approx. 15 m Warm light
ESC	1/5 ~ 1/20.000sec.
Weight	0.765 kg
SDK	upon request
Text overlay	Switchable on/off
Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request

# eneo IND-58F0002MTDA

Continuation of the specifications

Housing type	Outside
Housing material	Aluminium
Camera Type	Panoramic camera
Power consumption	8.88 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67, NEMA 4X
Power supply	12VDC, Poe
Temperature Range (Operating)	-30°C ~ +60°C, @ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	D-WDR
<b>Camera</b>	
Backlight compensation	Yes
Resolution standard	8 MP
Recording sensor	CMOS
Chip size	1/2,7"
Flickerless function	Yes
Camera shape	Minsters
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Day/night mode	Day,Night,Automatic,Time
White balance	Automatic,Manual
Photosensitivity	0,001 Lux bei F1,6
System	24h Color, True Day&Night
Day/night switching	Electronic
<b>Display</b>	
Image resolution max.	5120x1440
<b>DORI</b>	
Watch (62px/m)	23,8 m
Detect (125px/m)	11,7 m
Identify (250px/m)	5,5 m
Perceiving (25px/m)	60,1 m
<b>Functions</b>	
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,Red & blue flashing lights,Siren,Cloud Upload
Audio	2 Way Audio, Built-in microphone, Built-in speaker

# eneo IND-58F0002MTDA

Continuation of the specifications

Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
Internal memory	microSD card slot
<b>Notes</b>	
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results, use only eneo components. For mixed brands, we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
<b>Interfaces / Inputs/ Outputs</b>	
Alarm inputs	0
External connections	RJ-45, 12VDC input (DC plug), connection cable approx. 30cm, micro SD card slot 256 GB
Control Interfaces	Ethernet
<b>Parts supplied</b>	
Scope of delivery	manual, bag of screws
<b>Network</b>	
Network Protocols	DDNS, DHCP, DNA, FTP, HTTP, HTTPS, IEE 802.1, IPv4, IPv6, NTP, PPPoE, RTP, RTSP, SMTP, TCP-IP, UDP, UPnP
<b>Lens</b>	
Horizontal angle of view	180°
Focal length	2,8 mm
Aperture Range (F)	F1,2
MOD (Minimum Object Distance)	2 m
Lens Type	Prime lens
Zoom Factor (Digital)	0
<b>Video</b>	
Image transfer rate max.	15 fps
Resolution (extended)	5120x1440, 4608x1296, 4096x1152, 3840x1080, 3072x864, 1536x432, 1024x288
Picture size	32:9
Data stream types	Dual Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
<b>Product labeling:</b>	
EAN/GTIN	4260229840726
Manufacturer order number	238644
Series	eneo IN-Serie

## Optional Accessory

## eneo IND-58F0002MTDA

SKU	Name	Description
-----	------	-------------

## eneo IND-58F0002MTDA

### Continuation of accessory

233754	eneo AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	eneo AK-21	Camera connection box for Wall and ceiling mounting, Bullet and Dome Cameras IN series
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
236663	eneo DOME-WB8	Wall bracket for PTZ dome INP-54M2812M0A and IND-5 Dome Series
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products

### Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

### Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

