SOL-VICAM-MOBILE-LTE

SKU: 238675

INB-68M2812MFA, Junction box 3840 x 2160, 24h Farbe, IR, LTE, Varifocal lens 2,8 - 12 mm, WDR

Main Features

Portable video surveillance incl. connection cable	Applicable for construction sites
1/2,8" Sony STARVIS CMOS-Sensor, 8MP/30fps	Effortless mounting/demounting
Plug & Play	Remote access with QR-Code
Incl. 5m power supply cable with device connector	INB-68M2812MFA
Dimensions: 300 x 200 x 400 mm	SIM card not included
Wireless connectivity with LTE	Antenna does not support WLAN

Specifications

Series	Solvido WDR cameras
Camera Type	Face recognition, Intrusion Detection, People Count, Retail Intelligence
Resolution Standard	8 Megapixel
System	24h color
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	3840x2160
Image Transmission Rate	30 fps

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved

SOL-VICAM-MOBILE-LTE

Continuation of the specifications

Day&Night switch	ICR
Sensitivity	0,002 Lux bei F1,0
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	120dB
Motion Detector	yes
Lens Type	Varifocal (motorized)
Focal Length	2,8 - 12 mm
Digital Zoom	yes
Horizontal Angle of View	107 - 34°
Ilumination	Infrared, White light
Housing	Outdoor
Color (housing)	RAL9003
Hosuing material	Aluminium
Heater	no
Video outputs	no
Alarm inputs	ja
Audio support	yes
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Supply voltage	230VAC
Operating temperature	-30°C ~ +50°C
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Protection rating	IP66
Camera type	Bullet
Remote configuration	Browser
Illumination range	approx. 35m IR, approx.30m White Light
Manufacturer order number	238675

Optional Accessory

SKU	Name	Description
212371	SOL-WST-MB-20	Mastbefestigung 20cm für SOL-IQbox-mini, Set (2St)
209743	SOL-WST-WB	Wall mounting for CUS-WST and SOL-IQbox series set (4pcs) wall clearance 10mm

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved

SOL-VICAM-MOBILE-LTE

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved