



eneo INP-75A0033MIB

SKU: 240083

EAN: 4260229840665



Network PTZ Dome Camera, 33x AFZ, 2952x1944, Day & Night, WDR, AI 4,3-142mm, Alarm, Audio, IR, 12VDC, PoE+, IP66

Main Features

- 1/2.7" CMOS sensor, maximum resolution 5 MP/30fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR Noise Reduction
- Motorized autofocus zoom lens 33x 4.3-142mm
- Smart Codec H.265/H.264, multi-streaming
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Supports ONVIF profiles S/T/G/M
- Local storage via Micro SD card
- Audio input and output, NDAA conform
- Power supply 12VDC, or PoE IEEE 802.3at
- IR LED illumination, IP66
- Wall bracket included

Specifications

General	
Heating	No
Audio compression	G.711
Lighting	Infrared
Dimensions (WxHxD) (extended)	206,4x351,8mm
Illumination range	Approx 150m
ESC	1/5 ~ 1/20.000sec.
Weight	3.7 kg
SDK	upon request
Text overlay	Switchable on/off

eneo INP-75A0033MIB

Continuation of the specifications

Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request
Housing type	Outside
Housing material	Aluminium
Camera Type	Domecamera
Power consumption	25.6 W
Mounting type	Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3at
Protection	IP66
Power supply	12VDC, PoE+
Temperature Range (Operating)	-30°C ~ +60°C,@ Luftfeuchtigkeit 95% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	5 MP
Recording sensor	Chipset NT98528, CMOS, OmniVision OS05A20
Chip size	1/2,7"
Flickerless function	Yes
Camera shape	PTZ
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Day/night mode	Automatic,Night,Time
White balance	Automatic,Manual
Photosensitivity	0,003 Lux bei F1,6
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (62px/m)	42,5 - 1039 m
Detect (125px/m)	20,7 - 518 m
Identify (250px/m)	10 - 258 m
Perceiving (25px/m)	107 - 2574 m
Functions	
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes

eneo INP-75A0033MIB

Analysis	Abandoned and Removed Objects (SOD), Attendance (FA), Crowds (CD), Enter Region, Face Attributes (AD), Face Capture (FD), Face Recognition (FR), Heat Map (HM), Intrusion, Intrusion (PID), Leave Region, License plate recognition (LPD), License plate recognition (LPR), Line crossing (LCD), Manipulation (TD), Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD)
----------	---

eneo INP-75A0033MIB

Continuation of the specifications

Turning range	360
Alarm processing	recording internal storage (SD card),E-Mail,FTP,Cloud Upload
Audio	2 Way Audio
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
Tours	1 selectable tour
Speed (manual control)	200 °/sec
Speed (Target Approach)	200 °/sec
Internal memory	256GB, microSDHC card, microSDXC card
Notes	
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	RJ-45,Audio input,12VDC input (DC plug),Alarm in/output,micro SD card slot 256 GB,connection cable approx.45cm
Ethernet interface	100Base-TX, 10Base-T
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,wall bracket,4x heavy-duty anchors,1x Allen wrench,1x waterproof cover for RJ45 connector
Network	
Network Protocols	DDNS, DHCP, DNA, FTP, HTTP, HTTPS, IEE 802.1, IPv4, IPv6, NTP, PPPoE, RTP, RTSP, SMTP, TCP-IP, UDP, UPnP
Lens	
Horizontal angle of view	55 - 2,3°
Vertical angle of view	41,6 - 1,7°
Focal length	4,3 - 142 mm
Aperture Range (F)	F1.6
MOD (Minimum Object Distance)	1.5 m
Lens Type	Auto Focus Zoom
Zoomfactor (optical)	33
Video	
Image transfer rate max.	30 fps

eneo INP-75A0033MIB

Continuation of the specifications

Resolution (extended)	2592x1944 (4:3),2592x1520 (16:9),2048x1536 (4:3),2304x1296 (16:9),1920x1080 (16:9),1280x960 (4:3),1280x720 (16:9),640x480 (4:3),320x240 (4:3)
Picture size	16:9, 4:3
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
EAN/GTIN	4260229840665
Manufacturer order number	240083
Series	eneo IN-Serie

Optional Accessory

SKU	Name	Description
235562	eneo CM-22	Corner mounting adapter for wall bracket WB-24 and PTZ dome camera INP-75A0033MIB
238984	eneo DOME-CH7	Ceiling mount IN-Series Length approx. 294mm
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
239837	eneo KBD-3NET	Network keyboard with joystick, supports ONVIF protocol, RJ45, 12VDC
235257	eneo PM-21	Pole mounting adapter, steel for camera connection box AK-20, AK-21 and wall mount WB-24
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211124	PAINTING SERVICE PTZ dome or panoramic camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

eneo INP-75A0033MIB

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

