

ExCam IPQ1715 T08-VA2.2.K1.BOR-L.N-005.N-P

SKU: 240908



camera in stainless steel housing in accordance with RL 2014/34/EU (ATEX) and IECEx, 1080p, 20x optical zoom, IP68, -40°C/+60°C

Rack accessories are not included

Main Features

1/2.8" CMOS sensor with 2 MP (1920 x 1080)	Protection class IP66/68 (IEC 60529)
Powerful motorized zoom autofocus lens (21x optical)	H.265 video compression
AISI 316L stainless steel	Made in Germany
Certified for hazardous areas according to ATEX, IECEx, INMETRO, FM, Ex	Video compression H.265
Lightfinder and WDR	

Specifications

Series	ExCam
Camera Type	Explosionssgeschützt
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	Axis Zipstream, H.264, H.265, M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	60 fps
Day&Night switch	ICR
Sensitivity	0,1 Lux bei 50 IRE F1.5
Low Speed Shutter	yes

ExCam IPQ1715 T08-VA2.2.K1.BOR-L.N-005.N-P

Continuation of the specifications

Digital Noise Reduction	yes
Backlight Compensation	n/a
Wide Dynamic Range (WDR)	120dB
Motion Detector	yes
Lens Type	auto focus zoom
Focal Length	4 - 84,6 mm
Digital Zoom	no
Horizontal Angle of View	76 - 3,6°
Housing	Explosionssgeschützt
Color (housing)	Edelstahl
Hosuing material	Stainless steel
Heater	no
Video outputs	no
Alarm inputs	nein
Audio support	no
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Supply voltage	PoE
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Operating temperature	-40°C ~ +50°C
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Certifications	ATEX, EACex, IECEEx, INMETRO, MASC, UKEX
Protection rating	IP66/68
Manufacturer order number	22070401

Optional Accessory

SKU	Name	Description
240936	ExConnection Rail T04.5-D.BOR-4PoE++-100Base	High-performance PoE switch for the Ex area IP66-Base-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240937	ExConnection Rail T04.6-D.BOR-8PoE++-100Base	High-performance PoE switch for the Ex area IP66-Base-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240934	EXTB-3 Klemmkasten für ExCam Serie	Model: T12-M20-M20-M20
240932	Mastadapter PMB-VA1.x + VA.2.x	Compatible with all WMB wall brackets of the ExCam Series with the model codes T08-VA1.x, T08-VA2x and T03
240912	SKD02-T Kabel Kit 30 m	30 meter SKD02-T system cable Digital special cable with Ex approval according to DIN EN 60079-14
240913	SKDP03-T Kabel Kit 30 m	30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14

ExCam IPQ1715 T08-VA2.2.K1.BOR-L.N-005.N-P

Continuation of accessory

240915	Wandausleger WMB-VA2.0 / VA2.1 / VA 2.2	Steel) Compatible with housing sizes VA2.0 / VA2.1 Edelstahl VA2.2
240924	Wetterschutzdach WPR-VA2.2 (Edelstahl)	(Stainless Steel)

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

