



VM-UHD55MOH

SKU: 240950



55" (140cm) LCD Monitor, outdoor 4K UHD, 3840x2160, DisplayPort, HDMI, 3000nits, IP67/65, outdoor

Main Features

Professional 55" (140cm) LCD monitor	LED backlight
Maximum resolution 4K UHD 3840x2160 pixels	Digital 3D filtering and noise suppression
Suitable for outdoor use IP67/65	Designed for continuous operation 24x7x365
Contrast ratio typically 4,000:1	Versatile inputs DisplayPort, HDMI
Very high brightness 3,000 cd/sqm	Metal housing (suitable for industrial use)
Easy to read in bright sunlight	Further monitor sizes upon request

Specifications

Applications	Industry, Outside
Audio Inputs	no
Viewing Angle Horizontal	178 °
Viewing Angle Vertical	178 °
Screen diagonal (cm)	139.7 cm
Screen diagonal (inches)	55 1"
Fortification	VESA Standard 600x600mm
Video Inputs	Anti-glare display, Color TFT-LED, Hard coating (3H), Special Glass
Comb filter	No
Scope of delivery	manual,HDMI cable,power cord,IR remote controller

VM-UHD55MOH

Continuation of the specifications

Menu languages	English
Housing material	Metal
Brightness (typical)	3,000 cd/m²
Backlight	LED
Contrast ratio (typical)	4000:1
Manufacturer order number	240950
Response time (typical)	5 ms
Aspect ratio	16:9
Series	eneo Monitor
Control Interfaces	no
Video Inputs	DisplayPort, HDMI 2.0
Certifications	IK10,IP65,IP67

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

